

PLEC DE PRESCRIPCIONS TÈCNIQUES

CONTRACTACIÓ DE L'ACORD MARC PER A L'HOMOLOGACIÓ D'UN PROVEÏDOR PEL SUBMINISTRAMENT I POSTERIOR MANTENIMENT DE MATERIAL DE GAMMA BÀSICA PER A LABORATORIS D'OPTO-FOTÒNICA DE L'INSTITUT DE CIÈNCIES FOTÒNIQUES, MITJANÇANT PROCEDIMENT OBERT SUBJECTE A REGULACIÓ HARMONITZADA

NÚMERO D'EXPEDIENT: 2023.SU.005

Amb el suport de:

Índex

CLÀUSULA 1. Objecte del contracte.....	1
CLÀUSULA 2. Necessitats a satisfer amb la contractació	1
CLÀUSULA 3. Termini de vigència del contracte.....	1
CLÀUSULA 4. Especificacions tècniques. Productes a subministrar	2
CLÀUSULA 5. Pressupost del contracte, valor estimat i estimació del volum de contractació	2
CLÀUSULA 6. Adjudicació dels contractes basats en l'acord marc	3
CLÀUSULA 7. Transport i lloc del lliurament del subministrament	3
ANNEX 1	5

CLÀUSULA 1. Objecte del contracte

L'objecte del present Plec de Prescripcions Tècniques (PPT) que regula el present acord marc, és la consecució d'un marc homogeni per a poder valorar diferents ofertes que es presentin pel subministrament del material i equipament motiu de l'expedient de la contractació.

Totes les especificacions detallades al Plec de Clàusules Administratives Particulars i els requisits tècnics previstos en aquest PPT no tenen caràcter exhaustiu ni limitatiu, de manera que qualsevol altre element que l'empresa oferent consideri convenient, haurà d'incloure's i especificar-se en l'oferta presentada.

Així mateix, i donada la dificultat de relacions la totalitat dels béns necessaris pel correcte desenvolupament de les activitats d'investigació de l'ICFO, s'inclouen en el present acord marc tots aquells productes que, tot i no estiguin relacionats al PPT ni al contracte formalitzat amb els diferents adjudicataris, estiguin inclosos en els codis CPV 3800000-5; 38516000-5; 38600000-1; 38636000-2; 38636100-3 i 42610000-5, i estiguin destinats a la seva utilització en activitats d'investigació.

Sense perjudici de l'anterior, s'ha elaborat una llista dels materials més freqüents que previsiblement seran objecte de subministrament per part de l'empresa adjudicatària. S'adjunta l'esmentada llista com a Annex 1.

L'acord marc comprèn la determinació de les especificacions dels productes a subministrar i altres condicions generals del subministrament, així com la definició dels termes als quals s'han d'ajustar els contractes basats en aquest acord marc.

CLÀUSULA 2. Necessitats a satisfer amb la contractació

L'ICFO disposa de multitud de laboratoris destinats a la investigació en el camp de la fotònica, i que es divideixen en projectes d'òptica molt variats. Per tal de donar compliment als objectius de la institució i de satisfer les necessitats derivades de les exigències de cadascuna de les línies d'investigació que segueix la institució, es fa necessària l'adquisició de material de gamma bàsica pels laboratoris d'opto-fotònica.

Amb el subministrament del material exposat al punt anterior, es satisfaran directament els interessos de la institució, i es permetrà dotar els equips d'investigació del material necessari per tal de desenvolupar les seves tasques.

CLÀUSULA 3. Termini de vigència del contracte

El present acord marc tindrà una durada de **DUES (2) anualitats**. El dies a quo es produirà a partir del **dia 1 de juny de 2023**, o en el seu defecte, des de l'endemà de la formalització del contracte corresponent amb l'empresa que resulti adjudicatària de l'acord marc.

El contracte podrà ser objecte de pròrroga per DUES (2) anualitats addicionals, d'acord amb allò establert a l'article 29 LCSP.

Amb el suport de:

CLÀUSULA 4. Especificacions tècniques. Productes a subministrar

L'objectiu del present apartat és realitzar una relació orientativa i en cap cas exhaustiva, dels productes que s'inclouran a l'acord marc.

Degut a la complexitat, varietat i peculiaritats dels productes inclosos, resulta impossible adjuntar una relació detallada de tots i cadascun dels productes inclosos en el present acord marc, sense perjudici dels productes relacionats a l'Annex 1, així com tampoc es pot definir una quantitat exacta d'unitats a subministrar, doncs aquesta es troba sotmesa a les necessitats reals de l'ICFO en cada moment determinat.

Adicionalment, es podran incloure al present acord marc altres subministraments de gamma bàsica pels laboratoris d'opto-fotònica que, per la seva naturalesa especial vinculada a la recerca i investigació i que de manera imprevista i excepcional es requereixin per l'ICFO, i que no s'hagin previst expressament a l'acord marc.

Així mateix, s'inclouen també en el present acord marc tots aquells productes que, no havent-se relacionat explícitament en el quadre que tot seguit s'exposa, estiguin inclosos en els codis CPV i estiguin destinats a la seva utilització en activitats de recerca i investigació.

CLÀUSULA 5. Pressupost del contracte, valor estimat i estimació del volum de contractació

La despesa global derivada de l'acord marc no es pot concretar de manera anticipada, doncs la mateixa es configurarà per la despesa real acumulada per l'adquisició dels béns objecte del present contracte i durant el seu període de vigència.

Els contractes es tramitaran per l'ICFO mitjançant els corresponents expedients de despesa i finançant-se amb càrrec al crèdit pressupostari d'aquest, per la qual cosa les xifres indicades tenen un caràcter en cap cas vinculant, i sí orientatiu.

Per tant, no s'estableix un pressupost màxim de licitació en aquest procediment ja que el material a lliurar per l'empresa adjudicatària estarà supeditat a les necessitats que tingui l'ICFO durant la vigència del contracte.

No obstant l'anterior, i per facilitar que les empreses licitadores puguin efectuar un càlcul adequat de les seves ofertes en base a la despesa dels exercicis anterior i la projecció futura prevista, **s'estima un volum de contractació de 970.000 Euros per tota la durada del contracte, amb una contractació anual aproximada de 485.000 Euros** (IVA exclòs). Dit import, que constitueix el **pressupost base de licitació**, es desglossarà de la següent manera:

Expedient de contractació	Anualitat	Base imposable (IVA exclòs)	Total IVA (21%)	Total (IVA inclòs)
	2023 (6 mesos)	242.500,00 €	50.925,00 €	293.425,00 €
	2024	485.000,00 €	101.850,00 €	586.850,00 €
	2025 (6 mesos)	242.500,00 €	50.925,00 €	293.425,00 €
TOTAL		970.000,00 €	203.700,00 €	1.173.700,00 €

Amb el suport de:

El valor estimat del contracte, per tant, és de 1.940.000 Euros (IVA exclòs), els quals es divideixen segons el quadre següent per l'annualitat d'execució:

Valor estimat del contracte (sense IVA)					
2023	2024	2025	2026	2027	Total
242.500,00 €	485.000,00 €	485.000,00 €	485.000,00 €	242.500,00 €	1.940.000,00 €
242.500,00 €	485.000,00 €	485.000,00 €	485.000,00 €	242.500,00 €	1.940.000,00 €

Com s'ha indicat al PCAP, l'ICFO no resta obligat a exhaurir tot l'import, doncs els imports dels contractes basats en el present acord marc responen a necessitat no previsible i per aquest motiu, podrien aquests contractes ascendir a una quantitat inferior a la inicialment prevista.

CLÀUSULA 6. Adjudicació dels contractes basats en l'acord marc

L'adjudicació i homologació dins de l'acord marc no dona dret a la prestació dels subministraments. Aquesta prestació es produirà en el supòsit que l'empresa adjudicatària de l'acord marc resulti adjudicatària dels contractes basats, de conformitat amb el que es determina en els apartats següents.

Per contractació basada s'entén la contractació d'un o varis subministraments objecte del present Acord marc, que es prestaran de conformitat amb el que s'estableixi en el contracte basat, l'oferta de l'adjudicatari i a la documentació tècnica facilitada per l'ICFO.

L'adjudicació dels contractes basats en el present acord marc s'efectuarà aplicant els termes següents:

- 1) Donat que l'acord marc s'adjudica a un únic empresari, els contractes basats derivats de la licitació s'adjudicaran directament a l'esmentada empresa.**

La notificació a l'empresa adjudicatària de la resolució de l'adjudicació, que durà a terme l'ICFO, s'adjuntarà a la comanda realitzada per a la prestació del subministrament.

La notificació a la resta d'empreses no adjudicatàries del contracte basat, es durà a terme mitjançant la publicació del resultat al perfil del contractant de l'ICFO.

CLÀUSULA 7. Transport i lloc del lliurament del subministrament

Els productes es subministraran i lliuraran segons les necessitats de l'ICFO, al lloc de treball que s'indiqui en cadascun dels contractes basats que es formalitzin en base al present acord marc.

La logística de l'empresa i els seus mitjans de transport hauran d'assegurar el compliment dels subministraments en els termes i condicions explicitats al present PPT.

Tots els subministraments es realitzaran amb ports a càrrec dels subministradors i, en cas de disconformitat amb el producte, s'admetrà devolució, amb despeses a càrrec del subministrador.

Amb el suport de:

Castelldefels, a data de la seva signatura digital

Sr. Santiago Martín
Purchasing - ICFO

Amb el suport de:

ANNEX 1

ITEM DESCRIPTION
10 Pack of Ø1" Protected Silver Mirror
10 Pack of Ø1" Broadband Dielectric Mirror
10 Pack of Ø25.4mm Broadband Dielectric Mirror-
Mounted Ø25.0 mm Wire Grid Polarizer, 250 nm to 4 microns
BaF2 Holographic Wire Grid Polarizer Ø25 mm, Mounted
25.4mm, Mounted Zero Order 1/2 Waveplate 1064nm
Reflective Fiber Optics Collimator with Parabolic reflector
Tandem Narrowband Adj Opt Isol 780nm 5mm CA VLP
100X Mitutoyo Plan-Apochromat Objective, 0.70 NA, 6.0 mm WD
Reflective Fiber Optics Collimator for optomechanical system
10 Pack of Ø25.4mm Broadband Dielectric Mirror
785nm Coated Notch Filter 50%Band Width = 33nm
1/2" Compact Rotation Mount
Ø 25.4 mm Mirror, Broadband -E02 Coated
10 Pack of Ø1" Protected Gold Mirror
Reflective Objective, 40X, Silver Coated
30mm Cage Mounted Non-Pol BS Cube 50:50 400-700nm, M4 Tap
25.4mm Mounted Zero Order 1/2 Waveplate 808nm
Mounted Zero Order 1/2 Waveplate 850nm
Mounted VIS Linear Polarizer, 12.5mm OD
Narrowband Adj Opt Iso; 3mm; 1064nm; HP
12X Zoom - 6.50X Zoom Lens with 12mm Fine Focus
Mounted Zero Order 1/2 Waveplate 1550nm
Mounted Ø=6.33mm, f=4.51mm, NA=0.55 D-ZLaF52LA Asphere,-A
Reflective Fiber Optics Collimator for optomechanical system
1/2" Achromatic λ/2 Wave Plate 1100-2000nm
Mounted UV Linear Polarizer, 25.0mm OD
25.4mm, Mounted Zero Order 1/2 Waveplate 1550nm
Ø25.4mm Mirror, Protected Silver
200mm EFL Tube Lens, -A Coated
10mm Polarizing Beamsplitter Cube 620-1000nm
Mounted Zero Order 1/2 Waveplate 633nm
Mounted Zero Order 1/4 Waveplate 633nm
30mm Cage Mounted Polarizing BS Cube 900-1300nm, M4 Tap

Amb el suport de:

25.4mm NP 50:50 Beamsplitter Cube 400-700nm
Ø1" LP Dichroic Mirror, 50% T/R at 490nm
Glan Thompson Polarizer 10 mm CA, - A Coat
Ø12.7mm CaF2 Window, 3mm Thick
Ø25.4 mm, RFL = 152.4 mm, 90° OAP, Protected Silver
30mm Cage Mounted Variable BS/Attenuator, 1200-1600nm, M4 Tap
Ø2" LP Dichroic Mirror, 50% T/R at 650nm
25.4mm Mounted Zero Order 1/4 Waveplate 808nm
Mounted Ø25.0 mm Wire Grid Polarizer, 420-700 nm
6X Zoom - 6.50X Zoom Lens with 12mm Fine Focus
25.4mm, Mounted Zero Order 1/4 Waveplate 1550nm
Narrowband Fixed FSI; 850nm 2.7mm, CA, VLP
Mounted AC254-100-A - Ø1.0" , efl=100mm
Ø1" LINEAR POLARIZER W/ NBK7 WINDOWS, 400-700nm
Mounted AC508-200-A - Ø2.0" , efl=200mm
D=25.4mm, F=30mm, Near IR Achromat, -B COAT
Mounted Multi Order 1/2 Waveplate 633nm
Narrowband Fixed FSI, 780nm, 2.7mm CA, VLP
30mm Cage-Cube-Mounted WireGrid PBS Cube 400-700nm, M4 Tap
50.8mm Elliptical Mirror, -E03 Coated
Narrowband Adj FSI; 1550nm, 3.6mm CA, VLP
30mm Cage Mounted Polarizing BS Cube 420-680nm, 8-32 Tap
Mounted Variable Circular ND, D=50mm, Continuous
Narrowband Adjustable FSI; 405nm, 2.7mm CA, PBS
30mm Cage Mounted Non-Pol BS Cube 50:50 1.1-1.6µm, M4 Tap
Mounted Microlens Array p=300µm, f=14.6mm, AR 400-900nm
Ø25.4mm Zerodur Broadband Mirror, -E02 Coated
1" mounted LCP half wave plate, 633nm
5mm Polarizing Beamsplitter Cube 420-680nm
10 Pack of Ø1" UV Enhanced Aluminum Mirror
Ø50.8mm Mirror, Broadband -E03 Coated
Mounted Achromatic Half-Wave Plate, 400 - 800 nm
Mounted Zero Order 1/2 Waveplate 808nm
Mounted Zero Order 1/2 Waveplate 405nm
Compensated Variable Retarder, 350nm-700nm, 0nm to 1λ Retard
Ø1" N-BK7 Window, -A Coated, 1mm Thick
Mounted Zero Order 1/4 Waveplate 1064nm
Mounted Zero Order 1/4 Waveplate 532nm
Protected Gold, 1 inch D-Mirror
50.8mm N-BK7 Broadband Precision Window, -B Coated

Amb el suport de:

Aspheric Lens, Ø18.0mm, EFL = 15.0mm, NA=0.534, -A Coating
25mm SPUTTERED EDGE PASS FILTER, LONGPASS 1100nm
Mounted AC508-100-A - Ø2.0" , efl=100mm
Ø50.8mm Mirror, Protected Silver
1/2" Achromatic λ/4 Wave Plate 690-1200nm
Ø25.4mm Mirror, Broadband -E03 Coated
Ø1" LP Dichroic Mirror, 50% T/R at 1000nm
Variable Circular ND, D=100mm, Continuous, ND=0-2.
Ø1" ZnSe Plate Beamsplitter, 1 - 12 μm, 5 mm Thick
Reflective Beam Expander 4x
Shear-Plate Assy, 25.4-50mm Beam
100mm EFL Tube Lens, -A Coated
10mm Polarizing Beamsplitter Cube 420-680nm
Compensated Variable Retarder, 350nm-700nm, 0nm to λ/2 Retar
Ø12.7mm Mirror, Broadband -E04 Coated
20.0mm NP 50:50 Beamsplitter Cube 400-700nm
2.00X Adapter
VIS - IR Linear Polarizer, 12.5mm OD
10 Pack of Ø12.7mm Broadband Dielectric Mirror
NIR Linear Polarizer, 12.5mm OD
Ø1" N-BK7 Window, 1mm Thick
Ø50.8 mm, RFL = 152.4 mm, 90° OAP, Protected Silver
165mm EFL Tube Lens, -A Coated
Mounted Ø=7.20mm, f=6.24mm, NA=0.40 D-ZLaF52LA Asphere,-B
Faraday Rotator, 633nm, 4.7mm
D= 25.4mm 14 pc N-BK7 Plano-Convex Lens Set; A Coat
Fiber Collimation Package, λ=1550nm, f = 37.13 mm, FC/PC
Ø50.8 mm, RFL = 101.6 mm, 90° OAP, Protected Gold
30mm 4-Port Prism/Mirror Cage Mount, M4 Tap
Premium Shortpass Filter, Cut-Off Wavelength: 750 nm
Anamorphic Prism Pair, -A Coated
30mm Cage Mounted Polarizing BS Cube 620-1000nm, 8-32 Tap
Box with 10 UV Reflective Filters, SM1 Mounted
Fiber Collimation Package, λ=780nm, f=18.40mm, FC/APC
Laser Line Filter, CWL=532nm, FWHM=1nm
Ø50.8mm Mirror, Protected Gold
Wollaston Prism MgF2, 1 deg 20' beam separation
30mm Cage Mounted Polarizing BS Cube 420-680nm, M4 Tap
IR Bandpass Filter, CWL= 1750nm, FWHM=500nm
Reflective Fiber Optics Collimator with Parabolic reflector

Amb el suport de:

Ø25.4 mm, RFL = 50.8 mm, 90° OAP, Protected Gold
Mounted AC254-200-A - Ø1.0" , efl=200mm
Fiber Collimation Package, $\lambda=532$ nm, f= 10.90mm, FC/PC
Dichroic Mirror,LP,1180nm,Ø,1in
Ø1" 50:50 UVFS Plate Beamsplitter, 350-1100nm, t=5.0mm
Wollaston Prism 20° Beam Sep -B COAT
Coupling Prism, GGG, 45-45-90
Triplet Fiber Optic Collimator, 543 nm, NA=0.25
0.50X Adapter
Mounted AC254-150-B - Ø1.0" , efl=150mm
Mounted AC508-250-A - Ø2.0" , efl=250mm
Ø2" SP Dichroic Mirror, 50% T/R at 950nm
25.4mm, Mounted Zero Order 1/2 Waveplate 633nm
25.4mm, Mounted Zero Order 1/4 Waveplate 1064nm
25.4mm, Mounted Zero Order 1/2 Waveplate 2020nm
Ø12.7 mm, RFL = 50.8 mm, 90° OAP, Protected Aluminum
Reflective Fiber Optics Collimator with Parabolic reflector
Cube Mounted Pellicle BS 45:55 400-700nm
10.0mm NP 50:50 Beamsplitter Cube 1100-1600nm
10.0mm NP 50:50 Beamsplitter Cube 700-1100nm
Ø1" LP Dichroic Mirror, 50% T/R at 950nm
Ø1" LP Dichroic Mirror, 50% T/R at 650nm
16mm Cage Mounted Polarizing BS Cube 1200-1600nm, M4 Tap
Ø 2.75" UVFS CF Flange, 30min WEDGE
Mounted AC254-030-A - Ø1.0" , efl=30mm
1" Pellicle Beamsplitter, R/T Ratio: 45/55
633nm Coated Notch Filter 50% Band Width = 25nm
25.4mm, Mounted Zero Order 1/4 Waveplate 532nm
50.8mm Protected Silver Elliptical Mirror
Set of 10 Mounted ND Filters
Dichroic Mirror,LP,1800nm,Ø,1in
1:1 Matched Achromatic Pair, f1=40 mm, f2=40 mm
1:1 Matched Achromatic Pair, f1=30 mm, f2=30 mm
1064nm Coated Notch Filter 50% Band Width = 44nm
25.4mm, Mounted Zero Order 1/4 Waveplate 780nm
Premium Longpass Filter, Cut-On Wavelength: 1000 nm
Premium Bandpass Filter, CWL: 800nm, FWHM: 40nm
Ø25.4mm Mirror, Protected Gold
Ø=9.24mm, f=4.51mm, NA=0.54, Mounted S-NPH1 Asphere, -B
25x36mm SP Dichroic Mirror, 50% T/R at 1180nm

Amb el suport de:

Glan Thompson Polarizer 10mm Aperture
25.4mm Broadband Dielectric Elliptical Mirror, -E02
25mm SPUTTERED EDGE PASS FILTER, LONGPASS 1500nm
Ø1" Round Wedge Prism
Mounted AC254-075-C - Ø1" , efl=75mm
50:50 Non-Polarizing Beamsplitter Cube, 700-1100 nm, 2"
Mounted Ø=6.50mm, f=18.40mm, NA=0.15 D-ZK3 Asphere, -A
Ø25 mm NIR Reflective ND Filter, OD: 0.3
Ø25 mm NIR Reflective ND Filter, OD: 1.0
1/2" High Power PBS Cube, 1064nm
Mounted LA1131-A, Ø1" f = 50.0 mm
Mounted Microlens Array p=150µm, f=4.1mm, chrome
Fiber Collimation Package, λ=635nm, f = 35.41 mm, FC/PC
Mounted Zero Order 1/4 Waveplate 808nm
SM05 Mounted Zero-Order HWP, 1550nm
5.0mm NP 50:50 Beamsplitter Cube 400-700nm
Ø1" Linear Polarizer with N-BK7 Protective Windows B Coating
λ=635nm, f = 35.41 mm, NA=0.25 SMA Fiber Collimation Pkg.
OD=2.0 Mounted Absorptive Neutral Density Filter
Fiber Collimation Package, λ=633 nm, f=4.43 mm, FC/PC
25.4mm Polarizing Beamsplitter Cube 620-1000nm
Fiber Collimation Package, λ=1064nm, f = 36.60 mm, FC/PC
SM05 Mounted Zero-Order QWP, 850nm
25.0mm Right-Angle Prism Mirror, Protected Silver
Ø=9.24mm, f=6.24mm, NA=0.40, Mounted H-LAK54 Asphere, -C
25.4mm 90:10 Non-Polarizing Beamsplitter Cube, 700-1100nm
Triplet Fiber Optic Collimator, 1550 nm, NA=0.28
Mounted Variable Circular ND, D=25mm, Continuous,
Mounted Variable Circular ND, D=25mm, Continuous,
Fiber Collimation Package, λ=1550nm, f=6.37mm, FC/APC
25.4mm NP 50:50 Beamsplitter Cube 700-1100nm
Ø=9.24mm, f=11.0mm, NA=0.26, Mounted D-K59 Asphere, -B
25.4mm E02 coated " D" shaped mirror
1/2" High Power PBS Cube, 405nm
Mounted Zero Order 1/4 Waveplate 850nm
Mounted Zero Order 1/4 Waveplate 1550nm
Shear-Plate Assy, 2.5-5mm Beam
Ø1" Germanium Broadband Precision Window, ARC: 7.0-12.0µm
Ø12.7mm Mirror, Broadband -E02 Coated
Mounted AC254-050-A - Ø1.0" , efl=50mm

Amb el suport de:

Microlens Array p=300μm, f=14.6mm, AR 400-900nm
Dichroic Mirror,LP,900nm,Ø,2in
Mounted AC254-040-A - Ø1.0" , efl=40mm
Ø1" UVFS Window, -B Coated, 1mm Thick
Mounted AC254-150-A - Ø1.0" , efl=150mm
Variable Circular ND, D=100mm, Continuous, ND=0-4.
OD=3.0 Mounted Absorptive Neutral Density Filter
D=25.4mm, F=50m, Cyl. Near IR Achromat, -B COAT
Protected Silver, 1 inch D-Mirror
D=50.8mm, F=200mm, Near IR Achromat, -B COAT
12.7mm Polarizing Beamsplitter Cube 1200-1600nm
60mm UV Right Angle Prism
Ø1" UVFS Window, -A Coated, 1mm Thick
12.7mm Polarizing Beamsplitter Cube 620-1000nm
Laser Line Filter, CWL=780nm, FWHM=10nm
10mm Polarizing Beamsplitter Cube 1200-1600nm
50.8mm Broadband Dielectric Elliptical Mirror, -E02
1" Beam Sampler, B Coating, UV Fused Silica
Ø25.4 F=1000.0 N-BK7 B Coated Plano Convex Lens
25.0mm Right-Angle Prism Mirror, Protected Gold
5mm Polarizing Beamsplitter Cube 620-1000nm
Ø50.8 mm, RFL = 381.0 mm, 15° OAP, Protected Silver
Mounted AC254-100-C - Ø1" , efl=100mm
10:90 (R:T) Non-Pol Beamsplitter Cube 700-1100 nm, 10mm
Ø25.4 F=75.0 N-BK7 B Coated Plano Convex Lens
Ø1" Linear Polarizer with N-BK7 Protective Windows C Coating
OD=5.0 Mounted Absorptive Neutral Density Filter
Premium Bandpass Filter, CWL: 405nm, FWHM: 10nm
OD=1.0 Mounted Absorptive Neutral Density Filter
1in Square Hollow Roof Mirror Protected Silver
Ø1" Wedged CaF2 Window
Mounted AC508-300-B - Ø2.0" , efl=300mm
20mm Protected Gold Right Angle Mirror
Dichroic Mirror,LP,505nm,Ø,1in
Premium Bandpass Filter, CWL: 810nm, FWHM: 10nm
Premium Longpass Filter, Cut-On Wavelength: 500nm
Ø=12.18mm, f=8.00mm, NA=0.50, Mounted D-LAK6 Asphere, -A
Ø50.8 mm, RFL = 50.8 mm, 90° OAP, 3mm Horizontal Hole, Gold
Premium Shortpass Filter, Cut-Off Wavelength: 1000 nm
12.7mm NP 50:50 Beamsplitter Cube 400-700nm

Amb el suport de:

50.8mm Square Broadband Dielectric Mirror, -E02 Coated
Premium Longpass Filter, Cut-On Wavelength: 850nm
Aspheric Lens, Ø10.0mm, EFL = 8.0mm, NA=0.547, -A Coating
Premium Longpass Filter, Cut-On Wavelength: 600nm
Premium Shortpass Filter, Cut-Off Wavelength: 700 nm
Birefringent Reticle
Ø2" LP Dichroic Mirror, 50% T/R at 490nm
Ø25.4 F=100.0 N-BK7 B Coated Plano Convex Lens
Laser Line Filter, CWL=460nm, FWHM=10nm
Linear Variable ND Filter 0.04 to 2.0, 25mm x 100m
10.0mm NP 50:50 Beamsplitter Cube 400-700nm
1" mounted LCP half wave plate, 780nm
Ø25.4 F=150.0 N-BK7 B Coated Plano Convex Lens
Ø1" ZnSe Broadband Precision Window, -E4 Coated
Fiber Collimation Package, λ=633 nm, f=7.93 mm, FC/PC
20mm Protected Silver Right Angle Mirror
Short Pass Filter, 900 nm cutoff
6 Hole Filter Wheel w/ Base Assembly & 5 NE Filte
Long Pass Filter, Cut-On Wavelength: 1100 nm
Fiber Collimation Package, λ=532 nm, f= 7.87mm, FC/PC
Fiber Collimation Package, λ=1550nm, f = 8.18 mm, FC/PC
Fiber Collimation Package, λ=1550nm, f = 4.67mm, FC/PC
50.8mm N-BK7 Broadband Precision Window, -A Coated
2" Beam Sampler, B Coating, UV Fused Silica
25x36mm 50:50 UVFS Plate Beamsplitter, 350-1100nm, t=1mm
Ø1" 50:50 R:T UVFS Plate Beamsplitter, 400-700nm, t=5mm
Ø12.7 mm, RFL = 15.0 mm, 90° OAP, Bare Gold
Ø 2.75" UVFS CF Flange, 30min WEDGE, -A Coated
Ø 2.75" UVFS CF Flange, 30min WEDGE, -B Coated
Mounted AC508-300-A - Ø2.0" , efl= 300mm
7 mm Protected silver mirror 2 mm thick
Ø1" SP Dichroic Mirror, 50% T/R at 605nm
Polka Dot Beamsplitter, 25.4mm Square, UVFS
Mounted AC508-180-A - Ø2.0" , efl=180mm
Ø1" Zero-Order Quarter-Wave Plate, unmounted, 633nm
Ø25.4 F=150.0 CaF2 D Coated Plano Convex Lens
Ø2" Linear Polarizer with N-BK7 Protective Windows B Coating
Ø1" SP Dichroic Mirror, 50% T/R at 950nm
Ø1" SP Dichroic Mirror, 50% T/R at 490nm
Ø1" UVFS Window, 1mm Thick

Amb el suport de:

Mounted Ø25.0mm 275-375nm, BandPass Color Filter
D=50.8mm, F=500mm, Near IR Achromat, -B COAT
BX07 Storage kit qty: 35, 1" Spherical Optics 26
Medium powder free latex gloves Qty: 100 gloves
Ø1" SP Dichroic Mirror, 50% T/R at 650nm
Silver Right Angle Prism Mirror, 10mm
Ø=9.24mm, f=6.24mm, NA=0.42, Mounted H-LAK54 Asphere, -A
1" Beam Sampler, A Coating, UV Fused Silica
Ø=9.24mm, f=6.24mm, NA=0.42, Mounted H-LAK54 Asphere, -B
Ø1" Mounted AC254-050-AB, f=50 mm, SM1-Threaded Mount
Ø1" Mounted AC254-030-AB, f=30 mm, SM1-Threaded Mount
Mounted AC254-200-C - Ø1" , efl=200mm
Mounted AC254-150-C - Ø1" , efl=150mm
Ø1/2" Zero-Order Half-Wave Plate, Mounted, 780nm
Ø=12.18mm, f=8.00mm, NA=0.50, Mounted D-LAK6 Asphere, -B
Mounted Ø=6.20mm, f=15.29mm, NA=0.16 D-ZK3 Asphere,-A
Ø25.4 F=150.0 N-BK7 A Coated Plano Convex Lens
Ø25.4mm Mirror, Broadband -E04 Coated
Ø25.4 F=200.0 N-BK7 A Coated Plano Convex Lens
Mounted Multi Order 1/2 Waveplate 1550nm
Mounted Multi Order 1/2 Waveplate 780nm
25.4mm E03 coated " D" shaped mirror
Ø1/2" Zero-Order quarter-Wave Plate,mounted,1064nm
Ø1/2" Zero-Order Half-Wave Plate, Mounted, 1550nm
Ø1/2" Zero-Order Half-Wave Plate, Mounted, 588nm
Ø1/2" Zero-Order Half-Wave Plate, Mounted, 532nm
Dichroic Mirror,LP,567nm,RCT,25x36mm
Mounted Multi Order 1/4 Waveplate 633nm
Mounted Multi Order 1/4 Waveplate 780nm
F2 Dispersive Equilateral Prism, 50mm
Mounted UVFS Plano-Convex Lens, Ø1" , f = 100mm, -A
TRITC/CY3.5 Em. Filter CWL=620 nm BW=52 nm
YFP Ex. Filter CWL=497 nm BW = 16 nm
25.4mm PBS Cube, 532nm
Mounted AC254-075-B - Ø1.0" , efl=75mm
Dichroic Mirror,LP,505nm,RCT,25x36mm
λ=1550 nm, f=37.00 mm, NA=0.24 SMA Collimation Pkg.
Mounted Ø=6.33mm, f=3.10mm, NA=0.68 D-ZK3 Asphere,-A
NG9 -A Coated, Mounted Absorptive ND FILTER
Ø25.4 F=150.0 N-BK7 C Coated Plano Convex Lens

Amb el suport de:

Mounted AC254-200-B - $\varnothing 1.0''$, efl=200mm
Mounted AC254-250-B - $\varnothing 1.0''$, efl=250mm
Mounted LA1131-B, $\varnothing 1''$ f = 50.0 mm
f=2.75 mm, NA=0.64, NA=0.64, Geltech Aspheric Lens, -A
20.0mm UV Enhanced Aluminum Right Angle Mirror
Linear Variable ND Filter 0.04 to 4.0, 25mm x 100m
$\varnothing 25.4$ mm, F=100.0mm, Visible Achromat
30mm Cage Mounted BB Dielectric Mirror -E03 Coated, M4 Tap
Mounted AC254-050-B - $\varnothing 1.0''$, efl=50mm
Short Pass Filter, 850 nm cutoff
30mm Cage Mounted BB Dielectric Mirror -E02 Coated 8-32 Tap
25.4mm 90:10 Non-Polarizing Beamsplitter Cube, 400-700nm
Fiber Collimation Package, $\lambda=543$ nm, f = 34.74 mm, FC/PC
25.4mm Polarizing Beamsplitter Cube 1200-1600nm
25.4mm Polarizing Beamsplitter Cube 420-680nm
$\varnothing 1''$ 50:50 UVFS Plate Beamsplitter, 600-1700nm, t=5mm
Silver Right Angle Prism Mirror, 5mm
$\varnothing 1''$ ZnSe Broadband Precision Window, ARC: 4.5-7.5 μ m
Laser Line Filter, CWL=632.8nm, FWHM=1nm
25.4mm 90:10 Non-Polarizing Beamsplitter Cube, 1100-1600nm
25.4mm NP 50:50 Beamsplitter Cube 1100-1600nm
Knife-Edge Right-Angle Prism, Dielectric Mirror,-E03 Coating
$\varnothing 50.8$ mm Mirror, Unprotected Gold
$\varnothing 25.4$ f=150.0 Mounted Rd N-BK7 A Coat Plano Convex Cyl Lens
$\varnothing 50.8$ mm, F=250.0mm, Visible Achromat
$\varnothing 50.8$ mm, F=150.0mm, Visible Achromat
$\varnothing 25.4$ F=40.0 N-BK7 A Coated Bi Convex Lens
Fiber Collimation Package, $\lambda=780$ nm, f=15.29 mm, FC/APC
Fiber Collimation Package, $\lambda=780$ nm,f=4.51 mm, FC/APC
Fiber Collimation Package, $\lambda=780$ nm, f=8.0 mm, FC/APC
2" Pellicle Beamsplitter; R/T Ratio 45/55 1000-2000
Shear-Plate, 10-25.4mm Beam
$\varnothing 25.4$ F=200.0 N-BK7 C Coated Plano Convex Lens
Bandpass Filter, CWL = 800 $\pm$ 8nm, FWHM = 40 $\pm$ 8nm
20mm Polarizing Beamsplitter Cube 420-680nm
35mm EFL, F/2.0, 2/3" Format Machine Vision Lens
Fiber Collimation Package, $\lambda=780$ nm, f=11.07 mm, FC/APC
Mounted Retro-Reflector, $\varnothing 25.4$ mm A Coat
$\varnothing 75.0$ F=85.0 N-BK7 C Coated Plano Convex Lens
25.4mm Protected Silver Elliptical Mirror

Amb el suport de:

Ø25.4mm F=-30mm UVFS A Coated Plano Concave Lens
Ø25.4 mm, RFL = 50.8 mm, 90° OAP, Protected Silver
20.0mm NP 50:50 Beamsplitter Cube 700-1100nm
10:90 (R:T) Non-Pol Beamsplitter Cube 1100-1600 nm, 20mm
Fiber Collimation Package, $\lambda=532$ nm, f= 10.90mm, FC/APC
Fiber Collimation Package, $\lambda=532$ nm, f= 7.87mm, FC/APC
OD=4.0 Mounted Absorptive Neutral Density Filter
12.7mm Polarizing Beamsplitter Cube 420-680nm
Mounted N-BK7 Bi-Convex Lens, Ø1" , f = 25mm, -B
Mounted AC254-300-A - Ø1.0" , efl=300mm
D=25.4mm, F=30mm, IR Achromat, -C COAT
D=25.4 F=50.0 UV CaF2 E Coated Plano Convex Lens
Ø2" 10:90 (R:T) UVFS Plate Beamsplitter, 400-700nm, t=8mm
Ø25.4 mm, RFL = 152.4 mm, 90° OAP, Protected Gold
Ø25.4 mm, RFL = 101.6 mm, 90° OAP, Protected Silver
Ø25.4mm F=-75mm UVFS B Coated Plano Concave Lens
Ø25.4 F=100.0 N-BK7 A Coated Plano Convex Lens
30:70 (R:T) Non-Pol Beamsplitter Cube, 400-700 nm, 12.7mm
Ø1" IR Gold-Coated Concave Mirror, 3mm Center Hole, f=100.0mm
H=20.0 L=22.0 f=50.0 N-BK7 B Coat Plano Convex Cyl Lens
Ø=9.24mm, f=7.50mm, NA=0.30, Mounted H-LAK54 Asphere, -B
10:90 (R:T) Non-Po Beamsplitter Cube 700-1100 nm, 12.7mm
Aspheric Lens, Ø12.5mm, EFL = 10.0mm, NA=0.545, -C Coating
1" Pellicle Beamsplitter, R/T Ratio: 45/55
Bandpass Filter, CWL = 1550, FWHM = 40
Ø25.4mm, F=-50.0mm, Visible Achromat
H=50.8 L=53.0 f=75.0 N-BK7 B Coat Plano Convex Cyl Lens
Linear Step ND Filter 0.1, 0.2, 0.3, 0.4, 0.5 0.8
MOUNTED ND FILTER - D=1.0
Bandpass Filter, CWL = 690, FWHM = 10
Mounted Ø=7.20mm, f=6.24mm, NA=0.40 D-ZLaF52LA Asphere, -A
3.5mm EFL, F/1.4, 1/2" Format Machine Vision Lens
Premium Bandpass Filter, CWL: 780nm, FWHM: 10nm
Mounted LA1484-B, Ø1" f = 300.0 mm
Ø12.7mm Zerodur Broadband Mirror, -E03 Coated
30mm Cage Mounted Protected Aluminum Mirror, M4 Tap
Ø19.0mm Broadband Mirror, -E03 Coated, Backside Polished
25x36mm Silver Mirror
Premium Longpass Filter, Cut-On Wavelength: 750 nm
Premium Longpass Filter, Cut-On Wavelength: 550nm

Amb el suport de:

Dichroic Mirror,LP,605nm,Ø,1in
Premium Bandpass Filter, Ø25 mm, CWL = 850 nm, FWHM = 10 nm
Premium Bandpass Filter, CWL: 850nm, FWHM: 40nm
SM1 Quick Change Mount for Thin Optics- Pair
Mounted Ø=6.20mm, f=15.29mm, NA=0.16 D-ZK3 Asphere,-B
Mounted Ø=6.50mm, f=18.40mm, NA=0.15 D-ZK3 Asphere,-C
Premium Shortpass Filter, Cut-Off Wavelength: 550nm
Premium Longpass Filter, Cut-On Wavelength: 800 nm
50.8mm N-BK7 Broadband Precision Window, -C Coated
25.0mm N-BK7 Right-Angle Prism, Uncoated
30mm Cage Mounted Protected Silver Mirror, M4 Tap
5mm Right Angle Prism Broadband Dielectric Mirror
NA=0.79, Ø25.4mm, F=16mm, B270 Asph Condenser, -B Coat
Premium Shortpass Filter, Cut-Off Wavelength: 600nm
Premium Shortpass Filter, Cut-Off Wavelength: 500nm
Premium Longpass Filter, Cut-On Wavelength: 700nm
Premium Shortpass Filter, Cut-Off Wavelength: 800nm
Premium Longpass Filter, Cut-On Wavelength: 450nm
SM1 Quick Change Filter Mount - Pair
f=80 mm, Ø12.7 mm, CaF2 Mounted Plano-Convex Round Cyl Lens
Ø12.7 F=20.0 N-BK7 B Coated Plano Convex Lens
Ø25.0mm 335-610nm,BandPass Color Filter
Fiber Collimation Package, λ=633nm, f=6.17mm, FC/PC
Fiber Collimation Package, λ=1310 nm, f=4.64 mm, FC/PC
Post Mount Assembly for NDC Filters
N-BK7 RA Prism, 20mm, -A Coated on hyp.
Ø25.4mm Mirror, UV Enhanced Aluminum
Ø25.4mm Mirror, Unprotected Gold
Mounted AC508-080-A - Ø2.0" , efl=80mm
Mounted AC508-075-A - Ø2.0" , efl=75mm
λ=633nm, f =18.24 mm, NA=0.15 SMA Fiber Collimation Pkg.
Fiber Collimation Package, λ=633 nm, f=10.99 mm, FC/PC
Fiber Collimation Package, λ=1550nm, f = 15.58 mm, FC/PC
Fiber Collimation Package, λ=1550nm, f = 18.75 mm, FC/PC
Large powder free latex gloves Qty: 100 gloves
Long Pass Filter, Cut-On Wavelength: 1500 nm
NG9-A Coated, Mounted Absorptive ND FILTER
Ø1" SM1-Threaded Mount NIR Absorptive Neutral Density Filter
N-BK7 RA Prism, 15.0 mm, AR Coating on Hyp.: -C Coat
Ø 1.5" UVFS VACUUM WINDOW, 30min WEDGE

Amb el suport de:

Short Pass Filter, 800 nm cutoff
Mounted LA1951-A, Ø1" f = 25.4 mm
Ø25.4 F=-50.0 N-BK7 B Coated Plano Concave Lens
D-0.4 Mounted Absorptive Neutral Density Filter
Ø25.4 F=-100.0 N-BK7 B Coated Plano Concave Lens
Fiber Collimation Package, $\lambda=633\text{nm}$, f = 18.24 mm, FC/PC
D=25.4 F=1000.0 UV CaF2 E Coated Plano Convex Lens
Ø2" UV Fused Silica Wedged Window
Machine Vision C-Mount Coupler
NG11 -B Coated, Mounted Absorptive Neutral Density
NG4 -B Coated, Mounted Absorptive Neutral Density
Ø12.7 mm, RFL = 15.0 mm, 90° OAP, Protected Silver
Ø12.7 mm, RFL = 50.8 mm, 90° OAP, Protected Silver
H=30.0 L=60.0 f=150.0 N-BK7 B Coat Plano Convex Cyl Lens
Mounted Ø=7.22mm, f=11.00mm, NA=0.25 D-ZK3 Asphere,-A
Mounted UV Metallic ND OD: 3.0
Ø12.7 mm, RFL = 25.4 mm, 90° OAP, Protected Silver
NG4-B Coated, Mounted Absorptive ND FILTER
NG4-B Coated, Mounted Absorptive ND FILTER
NG4-B Coated, Mounted Absorptive ND FILTER
MOUNTED ND FILTER - D=4.0
Mounted UV Metallic ND OD: 2.0
Mounted AC508-400-A - Ø2.0" , efl=400mm
60mm Right Angle Prism
Right Angle Prism Mirror, Protected Silver, L = 15.0 mm
D=25.4 F=200.0 UV CaF2 E Coated Plano Convex Lens
D=50.8mm, F=100mm, Near IR Achromat, -B COAT
Vacuum Pick-up Tool 10pc
Ø25.4 F=1000.0 CaF2 D Coated Plano Convex Lens
D=25.4 F=150.0 UV CaF2 E Coated Plano Convex Lens
Laser Line Filter, CWL=532nm, FWHM=3nm
Mounted AC508-750-A - Ø2.0" , efl=750mm
Mounted AC508-150-A - Ø2.0" , efl=150mm
Mounted 1" round 20° square diffuser
Ø25.4 F=250.0 CaF2 D Coated Plano Convex Lens
30mm 4-Port Prism/Mirror Cage Mount, 8-32 Tap
Mounted N-BK7 Plano-Convex Lens, Ø2" , f = 400mm, -A
Mounted LA1509-B, Ø1" f = 100.0 mm
D=50.8mm, F=250mm, Near IR Achromat, -B COAT
Ø25.4 F=125.0 N-BK7 A Coated Plano Convex Lens

Amb el suport de:

H=10.0 L=12.0 f=40.0 N-BK7 A Coat Plano Convex Cyl Lens
Ø1" Mounted AC254-150-AB, f=150 mm, SM1-Threaded Mount
Ø25.4 F=50.0 N-BK7 B Coated Plano Convex Lens
Mounted LA1172-B, Ø1" f = 400.0 mm
1" Beam Sampler, C Coating, UV Fused Silica
Parfocal Length Extender 15mm RMS Ext RMS Int
D=25.4 F=100.0 UV CaF2 E Coated Plano Convex Lens
Mounted N-BK7 Plano-Convex Lens, Ø1" , f = 500.0mm, -B
Mounted N-BK7 Plano-Convex Lens, Ø1" , f = 750.0mm, -B
Ø1" Positive USAF1951 Test Target
Ø25.4mm Mirror, Broadband -E01 Coated
25x36mm10:90 (R:T) UVFS Plate Beamsplitter,700-1100nm, t=1mm
Ø1" Mounted AC254-100-AB, f=100 mm, SM1-Threaded Mount
Mounted UVFS Plano-Convex Lens, Ø1" , f = 500mm, -A
Ø25.4 f=1000.0 Mounted Rd N-BK7 C Coat Plano Convex Cyl Lens
H=30.0 L=32.0 f=500.0 N-BK7 B Coat Plano Convex Cyl Lens
H=30.0 L=32.0 f=200.0 N-BK7 A Coat Plano Convex Cyl Lens
H=30.0 L=32.0 f=1000.0 N-BK7 B Coat Plano Convex Cyl Lens
H=30.0 L=32.0 f=100.0 N-BK7 B Coat Plano Convex Cyl Lens
H=30.0 L=32.0 f=200.0 N-BK7 C Coat Plano Convex Cyl Lens
H=30.0 L=32.0 f=100.0 N-BK7 C Coat Plano Convex Cyl Lens
25 x 36 mm 90:10(R:T)UVFS Plate Beamsplitter,400-700nm t=1mm
Ø25.4 F=175.0 N-BK7 A Coated Plano Convex Lens
Ø1/2" Wedged ZnSe Window
25.0mm Knife-Edge Right-Angle Prism Mirror, -P01 Coating
Ø12.7mm Zerodur Broadband Mirror, -E04 Coated
Ø25.4 F=750.0 N-BK7 B Coated Plano Convex Lens
MOUNTED ND FILTER - D=0.5
Ø25.4 f=500.0 Mounted Rd N-BK7 C Coat Plano Convex Cyl Lens
Ø25 mm -A Coated KG3 Colored Glass
Ø25.4 F=200.0 N-BK7 B Coated Plano Convex Lens
Ø25.4 F=300.0 N-BK7 B Coated Plano Convex Lens
2" Pellicle 8:92 Splitting Ratio
Ø25.4mm, N-BK7 Laser Window, 5mm Thick, 1047-1064 nm
Ø1/2" Longpass Dichroic Mirror, 50% Trans./Refl. at 505 nm
Ø1/2" Longpass Dichroic Mirror, 50% Trans./Refl. at 605 nm
Ø25.4 F=-75.0 N-BK7 B Coated Plano Concave Lens
Ø25.4 F=250.0 N-BK7 B Coated Plano Convex Lens
Mounted UV Metallic ND OD: 1.0
Ø25.4 f=1000.0 Mounted Rd N-BK7 A Coat Plano Convex Cyl Lens

Amb el suport de:

H=30.0 L=32.0 f=1000.0 N-BK7 A Coat Plano Convex Cyl Lens
Mounted AC254-300-B - Ø1.0" , efl=300mm
Ø25.0mm NG9 -A Coated, Absorptive Neutral Density Filter
Ø50.8 F=-150.0 N-BK7 B Coated Plano Concave Lens
Mounted UVFS Plano-Convex Lens, Ø1" , f = 200mm, -A
Ø25.0mm NG9 -B Coated, Absorptive Neutral Density Filter
Mounted LA4148, Ø1" f = 50.0 mm
Ø25.4mm Concave Mirror, f=100.0mm, UV Enhanced Aluminum
Mounted UVFS Plano-Convex Lens, Ø1" , f = 300mm, -A
50.8x50.8mm Protected Silver Coated Metallic Mirror
D=12.7mm, F=75mm, Near IR Achromat, -B COAT
Ø1/2" LP Dichroic Mirror, 50% T/R at 490nm
25 x 36mm 50:50 UVFS Plate Beamsplitter, 400-700nm, t=1mm
Mounted AC254-040-B - Ø1.0" , efl=40mm
Mounted AC254-100-B - Ø1.0" , efl=100mm
Mounted AC254-060-B - Ø1.0" , efl=60mm
F=75.6 H=25.4 L=28.0 BK7 A Coat Plano Convex Cyl L
Ø25.4 f=200.0 Mounted Rd N-BK7 A Coat Plano Convex Cyl Lens
Ø1" Sapphire Broadband Window, D Coated
Ø0.5" Mounted AC127-025-AB, f=25 mm, SM2-Threaded Mount
Optic Storage Box for Ten Ø1" Optics, Pack of 5
Mounted LA4725, Ø1" f = 75.0 mm
Ø1" 50:50 UVFS Plate Beamsplitter, 1.2-1.6µm, t=5mm
2° Round Wedge Prism
Mounted LA4380, Ø1" f = 100.0 mm
Ø25.4mm, f=40.0mm, Finite Triplet, Mounted -A Coated
Ø25.4mm F=200mm UVFS C Coated Plano Convex Lens
Ø25.4mm F=100mm UVFS B Coated Plano Convex Lens
D=25.4 F=500.0 CaF2 Plano Convex Lens
Ø50.8mm, F=100.0mm, Visible Achromat
Polka Dot Beamsplitter, 25.4mm Diameter, B270 Glas
Ø50.8mm, F=200.0mm, Visible Achromat
Ø50.8mm, f=180.00mm, Visible Achromat
Mounted AC254-400-A - Ø1.0" , efl=400mm
Ø25.4mm, UVFS Window, 5mm Thick, -C Coated
Ø1" UVFS Window, -C Coated, 1mm Thick
OD=8.0 Mounted Absorptive Neutral Density Filter
UV Aluminum, 1 inch D-mirror
Ø25.4 F=35.0 N-BK7 A Coated Plano Convex Lens
Ø25.4 f=50.0 Mounted Rd N-BK7 A Coat Plano Convex Cyl Lens

Amb el suport de:

Bandpass Filter, CWL = 700 ± 8nm, FWHM = 40 ± 8nm
Ø12.7mm Mirror, Broadband -E03 Coated
D-0.6 Mounted Absorptive Neutral Density Filter
D-0.5 Mounted Absorptive Neutral Density Filter
Mounted AC254-080-A - Ø1.0" , efl=80mm
Ø25.4mm, N-BK7 Window, 5mm Thick, -C Coated
Ø25.4mm UVFS BS Compensator Plate, 350-1100nm t=5mm
25.4mm Elliptical Mirror, -E03 Coated
Bandpass Filter, CWL = 1400, FWHM = 12
Ø25.4 F=60.0 N-BK7 B Coated Plano Convex Lens
Ø25.4mm F=175mm UVFS C Coated Plano Convex Lens
Mounted UVFS Plano-Convex Lens, Ø1" , f = 200mm
Ø25.4 F=175.0 N-BK7 C Coated Plano Convex Lens
Mounted AC254-250-A -Ø1.0" , efl=250mm
D=25.4mm, F=200mm, IR Achromat, -C COAT
Ø25.4mm F=150mm UVFS B Coated Plano Convex Lens
Ø25.4mm Broadband Mirror, -E03 Coated, Backside Polished
Laser Line Filter, CWL=635nm, FWHM=10nm
Bandpass Filter, CWL = 470, FWHM = 10
Ø50.8mm Plano Convex PTFE Lens, f=75mm
f = 3.3 mm, NA = 0.47 Mounted RPO Asphere, -A Coated
Bandpass Filter, CWL = 1550, FWHM = 12
Bandpass Filter, CWL = 1350, FWHM = 12
Bandpass Filter, CWL = 450, FWHM = 40
H=20.0 L=22.0 f=150.0 N-BK7 C Coat Plano Convex Cyl Lens
Ø25.4 F=250.0 N-BK7 A Coated Plano Convex Lens
Ø12.7mm Mirror, Protected Silver
Laser Line Filter, CWL=850nm, FWHM=10nm
H=20.0 L=22.0 f=25.0 N-BK7 B Coat Plano Convex Cyl Lens
50.8mm Square Silver Mirror, 3.2mm Thick
Ø=9.24mm, f=4.00mm, NA=0.60, Mounted ECO-550 Asphere, -A
Ø25.4 F=125.0 N-BK7 B Coated Plano Convex Lens
H=15.0 L=30.0 f=-20.0 N-BK7 A Coat Plano Concave Cyl Lens
D=25.4mm, F=125mm, Near IR Achromat, -B COAT
Ø25.4mm, N-BK7 Window, 5mm Thick, -B Coated
Ø25.4mm, UVFS Window, 5mm Thick
H=20.0 L=22.0 f=80.0 N-BK7 B Coat Plano Convex Cyl Lens
Laser Line Filter, CWL=532nm, FWHM=1nm
Mounted N-BK7 Plano Convex Lens, Ø1" , f = 35mm, -A
collimation attachment

Amb el suport de:

Ø=9.24mm, f=11.0mm, NA=0.30, Mounted TAC4 Asphere, -B
Ø25.4 F=175.0 N-BK7 B Coated Plano Convex Lens
Mounted LA1986-B, Ø1" f = 125.0 mm
Mounted LA1509-A, Ø1" f = 100.0 mm
Mounted N-BK7 Bi-Concave Lens, Ø1", f = -100mm, -A
5mm Right Angle Prism Broadband Dielectric Mirror
Bandpass Filter, CWL = 810, FWHM = 10
Bandpass Filter, CWL = 590, FWHM = 10
Ground Glass Diffuser, Ø2.0", 1500 GRIT
N-BK7 Right-Angle Prism, 12.5 mm
Mounting Fork for 2" Pellicles
Mounted LA1484-A, Ø1" f = 300.0 mm
Ø25.4mm, N-BK7 Window, 5mm Thick, -A Coated
Mounted LA1433-B, Ø1" f = 150.0 mm
Bandpass Filter, CWL = 620, FWHM = 10
Bandpass Filter, CWL = 530, FWHM = 10
Bandpass Filter, CWL = 800, FWHM = 10
Grating, Holographic, Reflective, 2400/mm, UV Opt
25.0mm UV Fused Silica Right-Angle Prism, Uncoated
Small powder free latex gloves Qty: 100 gloves
25.0mm Right-Angle Prism Mirror, Protected Aluminum
25.4mm x 50.8mm Beam Sampler
H=20.0 L=22.0 f=30.0 N-BK7 Plano Convex Cyl Lens
Ø6.0 F=10.0 UV Fused Silica Plano Convex Lens
Grating, Holographic, Reflective, 2400/mm, VIS Op
Mounted AC127-019-A - Ø0.5", efl=19mm
Adapter Plate 2 (Metric) for Ø1" Parabolic Mirrors
Ø=9.24mm, f=13.86mm, NA=0.18, Mounted D-ZK3 Asphere, -A
f = 18.4 mm, NA = 0.15, Mounted RPO Asphere, -B Coated
Adapter Plate 1 for Ø0.5" Parabolic Mirrors
Mounted Ø=6.20mm, f=15.29mm, NA=0.16 D-ZK3 Asphere, -C
Ø25.4mm, N-BK7 Window, 5mm Thick
Mounted Ø9.936 mm, f=8.00 mm, NA=0.5 D-ZK3 Asphere, -C
Ø25.4 mm Dielectric-Coated CC Mirror, 750-1100 nm, f=150mm
Ø25.4mm Concave Mirror, f=100.0mm, -E03 Dielectric Coated
Ø25.4mm, F=35.0mm, Visible Achromat
f=2.75 mm, NA=0.64, NA=0.64, Mounted Geltech Asphere, -B
Ø7mm Broadband Dielectric Mirror, 750-1100nm
UV Fused Silica Right-Angle Prism, 15.0 mm
Ø25.4 F=200.0 UV Fused Silica Bi Convex Lens

Amb el suport de:

H=7.0 L=14.0 f=7.7 N-BK7 B Coat Plano Convex Cyl Lens
UNMOUNTED 2x2" ABSORPTIVE ND FILTER, OD: 2.0
Mounted LA1951, Ø1" f = 25.4 mm
Ø25.4mm, F=45.0mm, Visible Achromat
Ø25.4mm, F=40.0mm, Visible Achromat
Ø25.4mm, F=50.0mm, Visible Achromat
Long Pass Filter, Cut-On Wavelength: 500 nm
Long Pass Filter, Cut-On Wavelength: 600 nm
Long Pass Filter, Cut-On Wavelength: 1450 nm
H=10.0 L=20.0 f=12.7 N-BK7 B Coat Plano Convex Cyl Lens
Short Pass Filter, 550 nm cutoff
Short Pass Filter, 1000 nm cutoff
Optic Tweezers w/ Polyolefin Tips
NG4-A Coated, Mounted Absorptive ND FILTER
Mounted Ø=4.70mm, f=6.20mm, NA=0.30 D-ZK3 Asphere,-A
D=12.7mm, F=19mm, IR Achromat, -C COAT
Mounted Ø=6.33mm, f=4.51mm, NA=0.55 D-ZLaF52LA Asphere,-B
NA=0.79, Ø25.4mm, F=16mm, B270 Asph Condenser
Mounted UV Metallic ND OD: 4.0
Webril Handi-Pads 4x4 100 Wipes
Mounted Ø=4.70mm, f=2.76mm, NA=0.26/0.52 D-ZLaF52LA ,-B
Ø25.4 F=60.0 N-BK7 C Coated Plano Convex Lens
Laser Line Filter, CWL=632.8nm, FWHM=3nm
6° Round Wedge Prism
10° Round Wedge Prism
Ø25.4 F=75.0 N-BK7 C Coated Plano Convex Lens
Mounted Ø1/2" Absorptive ND Filter, OD=1.3
Mounted Ø1/2" Absorptive ND Filter, OD=2.0
Mounted AC080-010-A - Ø8.0mm, efl=10.0mm
Mounted LA1509, Ø1" f = 100.0 mm
Ø25.4 F=75.0 N-BK7 A Coated Plano Convex Lens
Optically Clear Adhesive Tape, 2 mils thick ,20 Sheets
H=10.0 L=12.0 f=-15.0 N-BK7 A Coat Plano Concave Cyl Lens
Ø25.4 F=35.0 N-BK7 B Coated Plano Convex Lens
MOUNTED ND FILTER - D=1.3
Grating, Ruled, 1200/mm, 500nm Blaze, 12.7X12.7x6mm
Ø25.0mm Absorptive ND Filter ,ND=4.0
Ø25.0mm Absorptive ND Filter ,ND=0.6
Ø25.0mm Absorptive ND Filter ,ND=0.3
Ø25.0mm Absorptive ND Filter ,ND=1.0

Amb el suport de:

Ø25.0mm Absorptive ND Filter ,ND=0.4
Ø25.0mm Absorptive ND Filter ,ND=2.0
Ø25.4 F=40.0 N-BK7 B Coated Plano Convex Lens
Positive Concentric Circle test target, Ø25.4mm
H=10.0 L=12.0 f=20.0 N-BK7 A Coat Plano Convex Cyl Lens
Ø25.4 F=750.0 N-BK7 C Coated Plano Convex Lens
Ø12.7 F=15.0 N-BK7 B Coated Plano Convex Lens
Ø25.4 F=-500.0 N-BK7 B Coated - Meniscus Lens
Aluminum Right Angle Prism Mirror, 10mm
Ø25.4mm, F=100.0mm, N-BK7 Plano-CX Lens, 532/1064nm V Coat
Mounted UV Metallic ND OD: 0.4
Mounted UV Metallic ND OD: 0.3
Mounted UV Metallic ND OD: 0.5
Mounted UV Metallic ND OD: 0.2
Ø25.4 F=300.0 N-BK7 A Coated Plano Convex Lens
Ø12.7mm, N-BK7 Window, 3mm Thick, -A Coated
Ø25.4 F=400.0 N-BK7 B Coated Plano Convex Lens
MOUNTED ND FILTER - D=0.1
MOUNTED ND FILTER - D=0.3
MOUNTED ND FILTER - D=0.4
MOUNTED ND FILTER - D=0.2
50.8mm Square Aluminum Mirror, 3.2mm Thick
Parfocal Length Extender 15mm M25 Ext M25 Int
Ø25.4 F=100.0 N-BK7 Plano Convex Lens
D-2.0 Mounted NIR Absorptive Neutral Density Filter
D-1.3 Mounted NIR Absorptive Neutral Density Filter
Ø12.7 F=30.0 N-BK7 B Coated Plano Convex Lens
Ø25.0mm NG4 -A Coated, Absorptive Neutral Density Filter
Ø25.0mm NG4 -A Coated, Absorptive Neutral Density Filter
Ø25.0mm NG1 -A Coated, Absorptive Neutral Density Filter
Ø25.0mm NG4 -A Coated, Absorptive Neutral Density Filter
Ø25.0mm NG4 -A Coated, Absorptive Neutral Density Filter
Ø25.0mm NG9 -A Coated, Absorptive Neutral Density Filter
Ø25.4 mm UV Enhanced Aluminum-Coated CC Mirror, f = 150 mm
Ø25.4 mm Silver-Coated Concave Mirror, f = 1000 mm
Ø25.0mm NG9 -A Coated, Absorptive ND Filter
Ø25.0mm NG11 -A Coated, Absorptive ND Filter
Ø25 mm AR-Coated Neutral Density Filter, 350-700 nm, OD: 1
Ø25.4 mm UV Enhanced Aluminum-Coated CC Mirror, f = 500 mm
Ø25.4 mm UV Enhanced Aluminum-Coated CC Mirror, f = 1000mm

Amb el suport de:

H=7.0 L=9.0 f=7.7 N-BK7 Plano Convex Cyl Lens
25.4x25.4mm Protected Gold Coated Metallic Mirror
Aspheric Condenser Lens, NA=0.61,
Ø25.4mm Concave Mirror, f= 100.0mm, Protected Silver
Ø12.7mm Concave Mirror, f=50.0mm, -E03 Dielectric Coated
Ø12.7mm Concave Mirror, f=25.0mm, -E03 Dielectric Coated
NA=0.79, Ø25.4mm, F=16mm, B270 Asph Condenser, -A Coat
Ø=2.40mm, f=1.45mm, NA=0.58 D-ZK3 Asphere,-A Coated
D-0.3 Mounted Absorptive Neutral Density Filter
Additive Dichroic Color Filter, Red, Ø1"
Subtractive Dichroic Color Filter, Magenta, Ø1"
Mounted N-BK7 Bi-Convex Lens, Ø1" , f = 75mm, -C
Gold coated N-BK7 ground glass diffuser, 1500 grit
Laser Line Filter, CWL=1550nm, FWHM=40nm
Laser Line Filter, CWL=635nm, FWHM=10nm
UV Metallic ND OD: 1.0
Ø50.8 F=60.0 N-BK7 C Coated Bi Convex Lens
Laser Line Filter, CWL=780nm, FWHM=10nm
Mounted LA1951-B, Ø1" f = 25.4 mm
Mounted LA1608-A, Ø1" f = 75.0 mm
Mounted LA1433-C, Ø1" f = 150.0 mm
Mounted N-BK7 Bi-Convex Lens, Ø1" , f = 75mm, -B
Mounted N-BK7 Bi-Convex Lens, Ø1" , f = 75mm, -A
Ø50.8 F=60.0 N-BK7 A Coated Bi Convex Lens
Ø25.4 F=75.0 N-BK7 Bi Convex Lens
Mounted LA1074-A, Ø1/2" f = 20.0 mm
30mm Cage Cube Connector
Ø50.8 F=100.0 N-BK7 A Coated Bi Convex Lens
Mounted N-BK7 Plano-Convex Lens, Ø1" , f = 750.0mm, -C
Mounted LA1708-A, Ø1" f = 200.0 mm
Ø25.4 F=100.0 N-BK7 Bi Convex Lens
Mounted LA1172-A, Ø1" f = 400.0 mm
Mounted N-BK7 Plano-Concave Lens, Ø1", f = -100mm, -B
Mounted N-BK7 Plano-Convex Lens, Ø1" , f = 500.0mm, -A
Mounted LA1461-B, Ø1" f = 250.0 mm
NA=0.76, Ø50.8mm, F=32mm, B270 Asph Condenser
Ø50.8 F=200.0 N-BK7 C Coated Plano Convex Lens
Ø25.4 F=300.0 N-BK7 Bi Convex Lens
Ø50.8 F=150.0 N-BK7 C Coated Plano Convex Lens
Mounted N-BK7 Plano-Concave Lens, Ø1/2", f = -25mm, -A

Amb el suport de:

Mounted N-BK7 Plano-Concave Lens, Ø1/2", f = -30mm, -A
GRIN Lens, Ø1.8, 0.29 Pitch, f= 1.90 mm, 630 nm
Ø50.8 F=100.0 N-BK7 B Coated Plano Convex Lens
Ø50.8 F=125.0 N-BK7 B Coated Plano Convex Lens
Ø12.7mm Concave Mirror, f= 50.0mm, Protected Aluminum
Ø1/2" Concave Mirror, f=9.5 mm, -G01 Coated
Ø50.8 F=150.0 N-BK7 B Coated Plano Convex Lens
Ø25.4 F=25.4 N-BK7 B Coated Bi Convex Lens
Ø25.4 F= -30.0 N-SF11 B Coated Plano Concave Lens
Ø25.4 F=500.0 N-BK7 Plano Convex Lens
Ø25.4 F=300.0 N-BK7 Plano Convex Lens
Ø25 F=-100.0 N-BK7 B Coated Plano Concave Lens
Mounted N-BK7 Bi-Convex Lens, Ø1" , f = 50mm
Ø25.4 F=1000.0 N-BK7 Plano Convex Lens
Ø25.4 F=25.4 N-BK7 C Coated Plano Convex Lens
Ø25.4 F=35.0 N-BK7 C Coated Plano Convex Lens
25mm VG9 Colored Glass Bandpass Filter
Mounted N-BK7 Bi-Convex Lens, Ø1" , f = 75mm
Ø25.4 F=300.0 N-BK7 C Coated Plano Convex Lens
Ø25.4 F=250.0 N-BK7 C Coated Plano Convex Lens
Mounted LA1540, Ø1/2" f = 15.0 mm
Ø25.4 F=25.4 N-BK7 B Coated Plano Convex Lens
Ø25.4 F=100.0 N-BK7 B Coated Bi Convex Lens
Ø25.4mm, F=30.0mm, N-BK7 Plano-CX Lens, 532/1064nm V Coat
Ø25.4 F=100.0 N-BK7 C Coated Plano Convex Lens
Mounted Frosted Glass Alignment Disk Ø1" w/Ø1mm Hole
Ø25.4 F=50.0 N-BK7 A Coated Bi Convex Lens
Ø25.4 F=-75.0 N-BK7 C Coated Plano Concave Lens
Ø25.4 F=-50.0 N-BK7 C Coated Plano Concave Lens
Adapter Plate 2 (Metric) for Ø2.0" Parabolic Mirror
Ø25.4 F=40.0 N-BK7 A Coated Plano Convex Lens
Ø25.4 F=60.0 N-BK7 A Coated Bi Convex Lens
Ø25.4 F=75.0 N-BK7 A Coated Bi Convex Lens
Ø25.4 F=125.0 N-BK7 C Coated Plano Convex Lens
Mounted LA1708, Ø1" f = 200.0 mm
Ø25.4 F=50.0 N-BK7 A Coated Plano Convex Lens
Mounted LA1461, Ø1" f = 250.0 mm
Mounted LA1484, Ø1" f = 300.0 mm
Ø25.4mm, F=50.0mm, N-BK7 Plano-CX Lens, 532/1064nm V Coat
Ø25.0mm Absorptive ND Filter ,ND=3.0

Amb el suport de:

Ø25.0mm Absorptive ND Filter ,ND=6.0
Ø25.0mm Absorptive ND Filter ,ND=0.5
Ø25.0mm Absorptive ND Filter ,ND=1.3
1" ROUND BG3 COLOR FILTER
Ø25.4 F= -25.0 N-SF11 Bi Concave Lens
Ø25.4 F=60.0 N-BK7 A Coated Plano Convex Lens
Ø50mm Plano Convex PTFE Lens, f=100mm @ 500GHz
Ø50mm Plano Convex PTFE Lens, f=300mm @ 500GHz
Ø12.7 F=25.0 N-BK7 A Coated Bi Convex Lens
Ø12.7 F=30.0 N-BK7 A Coated Bi Convex Lens
Ø12.7 F=40.0 N-BK7 A Coated Bi Convex Lens
Ø12.7 F=30.0 N-BK7 A Coated Plano Convex Lens
Ø12.7 F=-30.0 N-BK7 B Coated Plano Concave Lens
Ø12.7 F=40.0 N-BK7 A Coated Plano Convex Lens
Ø25 mm BG39 Colored Glass Bandpass Filter
UVFS Ground Glass Diffuser, Ø1.0", 1500 GRIT
Ø25 mm BG7 Colored Glass Bandpass Filter
Ø25 mm KG1 Colored Glass Bandpass Filter
25.4mm Dia. Square Mirror, 3.2mm Thick
Additive Dichroic Color Filter, Blue, Ø1"
Ø25.4 F=50.0 N-BK7 Bi Convex Lens
Adapter Plate 2 (Metric) for Ø0.5" Parabolic Mirror
Ø9.0 F=12.0 N-BK7 Bi Convex Lens
N-BK7 Bi-Concave Lens, Ø25.4 mm, f = -75.0 mm
Ø25.4 F=150.0 N-BK7 Bi Convex Lens
Positive Fresnel Lens, Ø1" , f =25mm
Ø25.4 F=150.0 N-BK7 Plano Convex Lens
Ø25.4 F=125.0 N-BK7 Plano Convex Lens
Ø25 F=-50.0 N-BK7 Plano Concave Lens
Ø25.4 F=-50.0 N-BK7 Plano Concave Lens
Ø25.4 F=-100.0 N-BK7 Plano Concave Lens
50.8mmX50.8mm ECONOMY VISIBLE LIGHT LINEAR POLARIZER
Ground Glass Diffuser, Ø1.0", 1500 GRIT
25.4mm Dia. Round Mirror, 3.2mm Thick
Optic Tweezers w/ Nylon Body
4X Super Apochromatic Objective
25.4mm PBS Cube, 633nm
10 Pack of Ø12.7mm Broadband Dielectric Mirror
Ø=6.50mm, f=18.40mm, NA=0.15 D-ZK3 Asphere,-C
Dichroic Mirror,SP,805nm,RCT,25x36mm

Amb el suport de:

Z Translator
Rotation Mount for 1/2 inch Optics
Ø31.8 mm Studded Pedestal Base Adapter, M6 Thread, 5-Pack
Flip Mount Adapter, Metric
Kinematic Mirror Mount for inch Optics
Metric Side Actuated Narrow 25mm X-Roller Bearing Stage
Rotation Stage For 25.4mm Optics
Adjustable 1" Iris
Small Univ. Clamping Fork. 1.24" counterbored slot, 5 pack
Metric Precision Cage Rotation Mount
Metric Lens mounting ring for 1" dia optic, 5 pack
Tech Spray Eco duster with Plastic nozzle, Euro Label
Small Univ. Clamping Fork w/ M6x1.0 captive screw, 5 pack
High Precision Translating Lens Mount for 1" Optics
Ø1.0" X 25.0 mm Pedestal Pillar Post, M4 x 0.7
Pedestal Base Adapter
Inline Cage Assembly Rotation Mount
Threaded Cage Plate
75mm Metric Post Holder Pack of 5
Metric Monolithic XY Translation Stage
Metric SM1 Right Angle Kinematic Mirror Mount w/ CBORES 30mm
50mm Metric Post Holder Pack of 5
Adjustable Height P-Post
20mm Metric Post Holder Pack of 5
Microscope Objective Adapter Ext. Tube
Ø12mm metric Iris housing, 5 pack
Metric Linear Translation Platform, 50mm, Side Actuated
Extension Rod 2 inch: Pack of 4
1/2" Keyed Rotation Mount
Beam Block (Active Area: 18 mm X 36 mm), Includes TR75/M Pos
Compact clamping fork, 0.375in slot, pack of 5
Kinematic Mirror Mount For 2" Optics
Metric Smooth Bore Kinematic Cage Block for 2" Elliptical
Two Adjuster 1" Low Distortion Optic Mount
12.7mm Dia . 20mm Long: Pack of 5 Post
Ø1.0" X 75.0 mm Pedestal Pillar Post, M4 x 0.7
54.7mm Pedestal Style Post Holder
12.7mm Dia . 50mm Long: Pack of 5 Post
44.7mm Pedestal Style Post Holder
Iris Diaphragm 1mm to 25mm Aperture

Amb el suport de:

Kinematic Prism Mount, Metric
12.7mm Dia . 75mm Long: Pack of 5 Post
Ø25.0mm X 50.0 mm Pedestal Pillar Post, M4 x 0.7
Pedestal Pillar Post , 50mm
Hex Drive Polaris Two Adjuster Kinematic Mirror Mount
Polaris Two Adj. Ø2" Low Distortion Mirror Mount w/out Knobs
XY Translator with Micrometer Drives
Metric Single Axis Translation Stage
Extension Rod 4 inch: Pack of 4
Precision Cage Rotation Mount
KM100 Kinematic Mirror Mount with Near IR Laser Qu
Ø25.0 mm Pedestal Pillar Post, M4 Taps, L = 65 mm
Kinematic Mirror Mount, Hex Adjuster
Kinematic Mirror Mount For 1" D-Shaped Mirros
0.50 SM1 Lens Tube, 5 pack
5-Axis Locking Kinematic Ø1" Optic Mount
High Precision Translating Lens Mount for 1 inch Ø
RS Series Spacer, 5mm
34.7mm Pedestal Style Post Holder
SMR1 Mounting Ring For SM1 Series
Cage Plate Stop ER Rod Compatible
38mm Solid Post 250mm Length
Kinematic Base Plate 50mm x 50mm x 25mm
Metric 30mm Cube Precision Rotation / Kinematic Platform
30mm Cage Mounted Ø20.0mm Iris
30mm Metric Post Holder Pack of 5
Pedestal Pillar Post , 25mm
Ø25.0mm X 50.0 mm Pedestal Pillar Post, M4 x 0.7
0.30 SM1 Lens Tube, 5 pack
Extension Rod 3 inch: Pack of 4
Pedestal Style Post Holder, 25.0MM
30mm to 60mm Cage Plate
38mm Solid Post 350mm Length
Large Univ. Clamping Fork. 1.76" counterbored slot, 5 pack
1 Inch Elliptical Metric Kinematic Corner Block
SM1 Threaded Lockable Rotation Mount for Ø1" Optics
Metric Elliptcal SM1 Right Angle Kinematic Cage Block
Kinematic Mirror Mount For Thin 1 inch Optics
12.7mm Dia . 30mm Long: Pack of 5 Post
12.7mm Dia . 40mm Long: Pack of 5 Post

Amb el suport de:

Ø25mm metric Iris housing, 5 pack
3/16 Black Hard Board, 3 Sheets 24x24
Kinematic Center Axis Mirror Mount For 1" Dia Optics, Metric
Left-Handed Kinematic Cylindrical Lens Mount
Compact clamping fork, M6 x 1.0 captive screw, 5 pack
Metric Right Angle Post Clamp, 5 pack
Metric Stackable Cage System Removable Filter Holder
P-Series Clamping Fork
Metric 2 Inch Precision Rotation Mount
Pedestal Pillar Post, 100mm
Kinematic Mounting Base 25mm Magnetically Coupled
Kinematic Mirror Mount Compact
50 MC-5 Lens Tissue in a Closeable Box
Quick-Release, XY Translating Lens Mount for Ø1in Optics
30mm Metric Post Holder
Kinematic Mirror Mount For 2 inch Optics
Metric Precision Rotation Mount for 0.5" Optics
Metric 1" D-Mirror Mount
SM05 to SM1 Adapter
Ø25.0 mm Pedestal Pillar Post, M4 Taps, L = 38 mm
45 Degree Mirror Holder For 1 Inch Kinematic Mirror Mount
Metric Kinematic Slip Plate
Slim Right Angle Bracket With Counterbored Slots
Non Rotating Adjustable SM1 Lens Tube
X-Y Axis Translation Stage w/ 360 deg. Rotation
Heavy Duty Lab Jack
X-Y Axis Translation Stage w/ 360 deg. Rotation
Lockable Kinematic 1" Optic Mount
Beam Trap, lab safety device, Absorbs Beam.
RS Series Spacer, 10mm
1.00 SM1 Lens Tube, 5 Pack
RS Spacer Kit, Metric
Fixed Ø1" Optical Mount, Metric 5-Pack
Post Clamping Mnt for Ø1/2" TR Series Posts, Flat Platform
KM100 Kinematic Mirror Mount with 1.2um to 1.7um L
Metric Z-axis Lens Translation Mount/Post Mount
Optic Adapter for 110,220,230,260,280,
Polaris Beam-Splitter Side Clamp in 1" Optic Mount
Lens Tubes Couplers 1.035-40 Threaded OD
Ø1/2in Metric Post Collar, 5 pack

Amb el suport de:

Ultra Stable Mirror Mount For 1 inch Optics
Iris Diaphragm used in SM2 series
Mounting Base, 25mm x 10mm Pack of 5
Black rubberized fabric
1" Lens Mount with SM1 External Thread
Pedestal Pillar Post , 75mm
Kinematic Grating Mount Adapter (20-40mm)
Adjustable Mechanical Slit
60mm Rotation Mount
6 Axis Lockable Ø1" Kinematic Mount
Pedestal Pillar Post, 38mm
Threaded Stainless Steel Iris, 12.0mm max. Aper.
Kinematic Center Axis Mirror Mount For 2" Dia Optics, Metric
Locking Kinematic Mount for Thin Optics
SM1 Series Quick Release Cage Mount
TR 90 Degree Flip Lens Mount
Universal Post holder adapter 5 Pack
1mm Jacketed Fiber Optic Storage Reel Pack of 10
Metric Translation Stage
Mounting base 1 x 3 x 0.39
Polaris Two Adjuster 1" Metric Platform Mount
Optic Table Balldriver Kit
Kinematic Mirror Mount For 1" Optics
37.5cm x 52.5cm x 30cm Black Hard Board Breadboard Enclosure
Clamping SM1 Cage Plate
Ø1.0" X 19.0 mm Pedestal Pillar Post, M4 x 0.7
Fiber Adapters
Metric Post End Clamp 0.5 inch, 5 pack
Vertical Cage Mounting Plate
1.00" Translation Stage with ¼-170 TPI Adjustment Screw
Kinematic Mirror Mount for Ø1/2" Mirror with Removable Knobs
Ø1.0" X 12.5 mm Pedestal Pillar Post, M4 x 0.7
1/2 inch Cage Translation Stage
Self-Centering Lens Mount, Ø3.8mm to Ø76.2mm, M4 Tap
Microscope Objective to SM1 Adapter
Metric, SM1, Right Angle Kinematic Mirror Mount, 30mm
Metric 30mm Cage Cube Rotation Platform
Ø15mm metric iris housing, 5 pack
Iris Diaphragm used in SM1 series
Fiber Collimation Adapter for SM1 Series Mounts

Amb el suport de:

1/2" Metric Translator Stage
12.7mm Dia . 150mm Long: Pack of 5 Post
38mm Solid Post 150mm Length
Kinematic Prism Mount, Metric
Ø25.0 mm Pedestal Pillar Post, M6 Taps, L = 155 mm
Adjustable Spanner wrench
Gimbal Mount For 50mm Optics
Left Kinematic Mirror Mount 1"D-Shaped Mir
Extension Rod 1 inch: Pack of 4
Mini Series Ø11mm Metric Kinematic Collimator Mount
1" Metric Beam Splitter/Right Angle Prism Mount
Clamp 'L' shape 0.68" x 0.75", 5 Pack
Kinematic Mirror Mount For Thin 2 inch Optics
12.7mm Dia . 100mm Long: Pack of 5 Post
Metric SMR2 Mounting Ring For SM2 Series
Rail Carrier, Counterbored Hole 1"x 1"
Extra Filter Holder Insert for Ø1" Optics
375mm Structural Rail
40mm Metric Post Holder Pack of 5
Cage Dichroic Filter Mount
SM1 Quick Release Adapter Set
SM1 Threaded Manual Beam Shutter
Adapter Plate M6 Taps
M4 Cap Screw Kit
30mm Cage Plate to RLA Rail Adapter
SM1 Threaded Precision Kinematic Mir
Light Tight/Reduced Stress Retaining Ring
38mm Solid Post 200mm Length
Metric Mounting Post Clamp
Thin Slip-On Post Collar For 1/2" Diameter Posts
1/2" XYZ Metric 30mm Cage Translator
Ø2" Outer Diameter Round Cage Plate, SM1 Internal Thread
Metric Dichroic filter mount 30 mm cage system
RS Series Spacer, 1mm
Mirror Holder for 1 inch Optics
Adapter w/ External C-Mount Threads and Internal SM1 Thread
Slip Plate Positioner Coarse 1mm X,Y pos.
Kinematic Mount for 1/2" Optics
Beam Trap, lab safety device, Absorbs Beam
6 hole Filter Wheel with Base Assembly

Amb el suport de:

Extension Rod .5 inch: Pack of 4
Metric Mounting Post Bracket
SM1 Series Variable Lens Tube 0.81" Travel
SM30 Lens Tube, 0.3in Long
Complete Metric Switchable Kinematic Base
Stackable lens tube for 2" optic-usable depth 1"
25.0 mm Pillar Post, M6 Taps, L = 100 mm, M4 Adapter Incl.
Metric Post Clamp with Large Mounting Plate
Rotation Stage For 25.4mm Optics w/ Calibrated Scale
Right Angle Post Clamp, Metric
1" Stackable Lens Tube
Tip Tilt Rotation Beam Steering Assembly
Iris Diaphragm 0.8mm to 12mm Aperture
Kinematic Cylindrical Lens Mount
Cage Plate Mounting Bracket
Ø25.0 mm Pillar Post, M6 Taps, L = 300 mm, M4 Adapter
Ø1" Clear Edge Kinematic Mirror Mount
Stackable lens tube for 2" optic-usable depth 1/2
Post : 12.7mm Dia . 20mm Long
SM1 Threaded Iris with Matching Aperture Size
P-Series Pedestal Base Adapter
3mm Jacketed Fiber Optic Storage Reel Pack of 10
Removable Filter Holder for Ø2" optics for 60mm cage, METRIC
SM1 Threaded Adapter for Ø4mm Cylindrical Components
15 Piece Metric Wrench Kit with Stand
SMA Fiber Adapter Plate with External SM1 (1.035"-40) Thread
RS Series Spacer, 3mm
Inline Cage Assembly Rotation Mount
Flip Mount Adapter
42mm Universal Cylindrical Lens Mount
Mounting post base, 61mm Dia X 12.7
Clamp 'L' Shape 0.81"x 0.75", 5 Pack
Metric Self-Centering Lens Mount
SM1 to SM2 Series Thread Adapter
Non-Anodized XE25 Extrusion, 2 Meters
Removable Plate Kinematic Mount
60mm Quick Release Cage Mount
Right Handed Front Rear Loaded Mirror Mount
Extension Rod 1.5 inch: Pack of 4
Cage Turret Mount

Amb el suport de:

45° Mount for 1" Elliptical Mirror
Spanner Wrench For SM1RR
Mounted Standard Iris, 15.0mm max. Aper.
Gimbal Mount For 1 inch Optics
Small Optical Rails 300mm
Black posterboard 20"x30"x1/16"
Large 60mm Cage Plate, Metric.
Optic Adapter for C240TM
79.7mm Pedestal Style Post Holder
Extension Rod 6 inch: Pack of 4
Ø20mm metric Iris Housing, 5 pack
300 mm Structural Rail
Lens mount for 25.4mm optic
1.5 inch Post Clamp Metric
Kinematic Mount Centering Plate
SM2 Int to SM1 Ext Adapter
Metric Lens mounting ring for 0.5" dia optic, 5 pack
Extension Rod 8 inch: Pack of 4
Adapter for 0.58 to SM1
Mounted Zero Aperture Iris, 25.0mm max. Aper.
Two Adjuster SM1 Threaded Kinematic Mirror Mount
Universal Metric Base Plate
UV Curing Optical Adhesives
Small Optical Rails 150mm
5 pack, Cable Straps, Hook and Loop Fastener 3/4 x 4
SM1 Lens Tube Clamp
Kinematic Rotation Mirror Mount For 1/2" Diameter optics
1" Lens Tubes Coupler with External SM1 Thread, 1" long
Stackable lens mount for 1" optic-usable depth 1/2
Pitch And Yaw Accessory Tilt Platform w/
Pitch And Yaw Accessory Tilt Platform w/micrometers
Ø1" Adjustable Lens Tube, 0.32" Travel Range
Two Adjuster Hex Driven 1" Low Distortion Optic Mount
Adjustable Prism Clamp
Cage Assembly Turret Mount 1" Optic
Centering Plate for 1" Kinematic Mirror Mount, Metric
Rotatable V-Clamp Cage Mount
Adapter for SM05 lens tubes to SM1 Threads
Thick SM05 Int. to SM1 Ext. Adapter
Telescoping Lens Tube 2" Travel

Amb el suport de:

Kinematic Mirror Mount For 2" Optics
RS Series Spacer, 2mm
50um Mounted Pinhole
22.5cm x 52.5cm x 30cm Black Hard Board Enclosure
Metric 14" Damped Post
Threaded Locking Kinematic Mount, 2" Thin Optics
Metric Coarse Adjustable Height Platform
Mounted Standard Iris, 20.0mm max. Aper.
Microscope Objective Adapter Ext. Tube
Medium Powder Free Nitrile Gloves, QTY 100
Metric Mounting Post V-Clamp
Clamping SM2 Metric Cage Plate
Cylindrical Lens Metric 60mm Cage Mount
Alignment Disk
Stackable Lens Mount For 1" Optic-Usable Depth 2"
M3 Hardware Kit for Mini Series
Clear Edge Kinematic Mount for Ø2" Optics
16mm Cage Rotation Mount
60mm Cage Mounted Ø50.0mm Iris
Metric Post Mounted 2" Kinematic Mirror Mount
SM2 Series Slim Slip Ring
40um Wide Slit, Mounted
9-Piece Color-Coded Hex Key Set, Metric
Adjustable Prism Clamp
SM1 Slotted lens tubes, 2in Thread depth
Post :12.7mm Dia . 250mm Long
4-Way Mounting Cage
Adapter with External SM1 Threads & Internal M25x0.75 Thread
225mm Structural Rail
Post 12.7mm Dia . 200mm Long
Table clamp 9.500mm x 13mm x 51mm, 5 pack
Post: 12.7mm Dia . 300mm Long
1.5" dia Mounting Post x 14"
1 Inch Stackable Lens Tube, 4 Inch Usable Depth
60mm Cage Assembly to P-Post Adapter, Metric
Fiber Collimation Adapter for SM1 Series Mounts
SM1 Series end Cap for Machining
XT66 & XT34 Vertical Breadboard Mount
Mini angle Bracket
Vacuum Epoxy

Amb el suport de:

Clamp 16mm x 16mm x 76mm, 5 Pack
1 inch Construction Cube, Clearance Holes
Post Collar
METRIC MAGNETIC PEDESTAL BASE
Ø1.27in Clamp for Cylindrical Objects
SM1 Fiber Clamp, 250 micron
Cylindrical Lens Metric 30mm Cage Mount
SM1 Series Slim Slip Ring
Extension Rod 12"
20 Drawer Cabinet
Metric RS-to-TR Right Angle Post Clamp
Metric, SM05, Right Angle Kinematic Mirror Mount, 16mm
Metric SM2 Right Angle Kinematic Mirror Mount w/ CBORES 60mm
Kinematic Mirror Mount For 1" Square Optics
Ring-Actuated SM05 Iris Diaphragm
1 Inch Stackable Lens Tube, 3 Inch Usable Depth
Drop In 30mm to 60mm Cage Adapter
Lens mounting ring 2" w/ External SM2 Thread
Lens mounting ring 2" w/ External SM2 Thread
38mm Solid Post 100mm Length
2.00 SM1 Lens Tube, 5 pack
Lens Tubes Couplers 1.035-40 Threaded ID
SM05 to 9mm Lens Cell Adapter
Metric Post Mounting Clamp, For 25mm Diameter Post
30mm Cage to RS-Post Clamp
Metric PM Mount for Metric TR Post
10 degree Back Reflecting Lens Tube
5um Mounted Pinhole
SM2 Quick Release Adapter Set
0.50M XT95 Rail
Differential Kinematic 1" Optic Mount
Mounted Standard Iris, 8.0mm max. Aper.
Threaded Zero Aperture Iris, 12.0mm max. Aper.
3 inch SM2 Lens Tube
Kinematic Mirror Mount For 1/2" Square Optics, Metric
Mounting Adapter for Mounting 1/2" Optic in 1" Mount
Kinematic Mirror Mount For 2" Square Optics
60mm Cage Plate with 2" Optic Mount
Digital Calipers
High Performance Black Masking Tape 1"

Amb el suport de:

M4x0.7 4mm Long Nylon tipped set screw, Pack of 10
2" Rotating Adjustable Focus 0.5" Travel
Metric XZ-Axis Adapter for XRN Series Stages
Kinematic Breadboard Seats
100um MOUNTED PINHOLE
Metric Adjustable Height Collar
60mm 6-Way Cube
38mm dia Solid Post 75mm Length
100mm Metric Post Holder Pack of 5
Kit: 4 Wash Bottles and 3 Plastic Dropper Bottles
90 deg Counter Bored Construction Post
20um Mounted Pinhole
Quick Release Square Filter Holder
Flip Platform for 1" (25mm) Post, Metric
Metric Benchtop Organizer
Two Adjuster 1/2" Mirror Mount
60mm Removable Cage Plate
5 pack lens tissues
Drop in SM1 Threaded Cage Plate
Ø25.0 mm Pedestal Pillar Post, M6 Taps, L = 90 mm
Two Adjuster SM05 Threaded Kinematic Mount
Rotation Maintaining Collar
Polaris 1/4-100-2B 13mm Lock Nut
Dual Lens Mount for Ø1" Optic, Metric
4-Way Mounting Cube
Metric Thread Adapter Kit
M4 to M6 Threaded Adapter
6.5mm Travel Mic. Head, Spherical Tip
Lens Tubes Couplers 1.000-32 x 1.00 Threaded OD
45 degree mounting adapter 50mm beam height
RS Series Spacer, 4mm
104.7mm Pedestal Style Post Holder
SM2 Series Extension Tube, 6"
End Cap External Threads
Stackable lens tube for 2" optic-usable depth 2"
1" D-Mirror Mount
1um Mounted Pinhole
ER-to-TR Right Angle Metric Post Clamp
SM1 Int to SM05 Ext Adapter
Male SM1 Quick Release Adapter Half

Amb el suport de:

XT95 100mm Rail Carrier
M3x0.5-4mm Long, Pack of 10
Extension Rod 24"
Metric Lens mounting ring for 2" dia optics, 5 pack
Left Handed Front Rear Loaded Mirror Mount
LMR1 Alignment Plate, 1"
0104-001 Rev D Clamp 3/8 x 5/8 x 1-3/8 , 1/4 x 7/8
Large Powder Free Nitrile Gloves, QTY 100
12.7mm Fiber Collimation to SM1 Adapter
2 inch Kinematic Prism Mount with M4 Taps
90 deg Tapped Bored Construction Post
M6 X 1.0 Stainless Steel Cap Screw 16mm Long Pack of (25)
600 mm Long Structural Rail
Pedestal Pillar Post, 19mm
Small Optical Rails 75mm
2 inch Diameter, Stackable Lens Tube, 0.30 inches
Mounted Stainless Steel Iris, 25.0mm max. Aper.
A/SS Post with Hex: 12.7mm Dia. X 15mm Long
Ø25.0 mm Pedestal Pillar Post, M6 Taps, L = 65 mm
Thermally Stable SM1 to RMS Adapter
Kinematic Pelical Mount for KM200 Series
M6 bolt kit over 1000 pieces
SM05 to SMA Fiber Adapter
Intersecting ER Adapter
Cage Plate Mounting Base 30mm
Rotation Beam Steering Base
SM1-Threaded Removable Mounting Carriage for Ø1" Optics, Mag
1/2 inch Diameter, Lens Tube, 0.30 inches long
Cotton Tipped Applicators, pack of 100
UV Curing Optical Adhesive
SM2 Coupler, External Threads
30 mm to 30 mm 90 Degree Cage Adapter PI
7664-001 Rev C & 7664-002 Rev B, Fixed Holder
Alignment Tool
Polarizer Mount for GL10 & GT10 Series
Slim Right Angle Bracket w/Counterbored Holes & M6, M4 Tap
Mirror Holder for Thicker Ø1 inch Optics
Calibrated Iris Diaphragm
Extension Rod 0.25 inch
2" Rotating Adjustable Focus 1" Travel

Amb el suport de:

500 mm Long Structural Rail
Ø11mm to Ø1/2" Barrel Adapter
MINI Ø0.50in FIXED METRIC OPTIC MOUNT
Snap-On 60 mm Cage Mounting Bracket for 66 mm Rails
Metric Post Mounted Removable Kinematic Lens Mount
External C-Mount to SM1 Thread Adapter
200um Wide Slit, Mounted
Mounting Base, 50mm x 75mm x 10mm Pack of 5
30mm Cage-SM1 Rotatable Lens Cell
5/64 Hex Key Thumb Screw
Cage Plate
Kinematic base plate 75mm x 75mm x 25mm
Metric 1" Fixed Mirror Holder
Cage Rotation Mount with Double Bore
Plate Holder
Polaris Beam-Splitter glue in 1" Optic Mount
12mm Collimation to 1" Adapter
Blank Cover Plate
Stackable 1.50" Lens tube
11mm Collimation to 1" Adapter
SM2 Spanner Wrench
Translating Post, 2"
External SM1 Thread to Ø1" Optic Mount Adapter
SM2 Threaded 1" Optic Adapter for LCP01 & LCP02
Matte Black Aluminum Foil, .002 x 12" x 50'
Mounting Post, Length=30 mm
Ø1" Mount Adapter for Ø2" Optic
M6 X 1.0 Stainless Steel Cap Screw 12mm Long Pack of (25)
30 mm to 60 mm 90 Degree Cage Adapter PI
Cage Plate for SM2 Lens Tube (Ø2.205" Clear Aperture)
Spanner Wrench For SM1 Adapters
End Cap SM1 Series
Ø30mm (SM30) Series Lens Tube Clamp
12.0mm Pedestal Post, M4 Setscrew, M6 Tap, L = 50mm
Button magnet, 0.260 in slot, 10 pack
Ø25.0 mm Pedestal Pillar Post, M4 Taps, L = 155 mm
10mm Fiber Collimation to SM1 Adapter
Cage Plate Moutning Base 60mm
SM1 Retaining Ring, 5mm Thick
12.7mm [0.50in] Beamsplitter Cube Adapter Mount

Amb el suport de:

30mm Cage Support to RLA Rail Adapter
Adjust lens mount for optic up to 46mm
Pedestal Post Clamp
Pedestal Pillar Post , 12.5mm
154.7mm Pedestal Style Post Holder
SM2 Internal thread to Ø2" Adapter
Lens Tubes Couplers 1.000-32 x 0.50 Threaded OD
Left-Handed Kinematic Mirror Mount For 1" Square Optics
90° Flip Mount for Rectangular Optics
45 Degree Angle Block, Counter bored
Ø1.5" Mounting Post X 12"
45° Angle Plate
Cage System U-Bench
Reaching 3 inch Post Joist Metric
Kinematic Pelical Mount for KM100 Series
High Performance Black Masking Tape 2"
Post : 12.7mm Dia . 30mm Long
3mm Jacketed Fiber Optic Storage Reel
Large 60mm Cage Plate
30mm Cage Assembly to P-Post Adapter, Metric
SM05 to 0.5" Thread Adapter
1 inch Construction Cube, Slotted corner
Small Powder Free Nitrile Gloves, QTY 100
Lens mount for 12.7mm optic
TR Series Spacer, 5mm, Pack of 5
Adapter w/ External SM2 Threads and C-MOUNT Internal Thread
Metric, 1" Diameter Slip Ring
60mm Removable Cage Segment Plate
Cage Mount for T03 Lasers
4mm Thick 30mm Threaded Cage Plate
10um Mounted Pinhole
Kinematic Breadboard Seat Bottom Set
Lens mounting ring for 1.5" dia optics Metric
Short Dovetail Tapped M6-1.0, 20mm Length
UV Curing Optical Adhesives
XT66 Double Dovetail Clamp, 20mm long
1.5" Post Holder with Spring-loaded Thumbscrew Pack of 5
Left handed Kinematic Mirror Mount for ½" D-shaped M, Metric
Dual SM1 Slip Plate Translator, Metric
Stackable Lens Mount For 1" Optic-Usable Depth 1"

Amb el suport de:

Iris Diaphragm 1.27mm to 36mm Aperture
SM2 Adapter for 32mm Optics
M6-1.0 x 10mm Metric Enclosure Screws, Box of 100
1.5" dia Mounting Post x 10"
Iris Diaphragm Aperature Mounted on a TR3
XT66 Rail Carriage
XT66 Rail Carriage
SM1 Slotted Lens Tube w/ Dust Cover
Blank Filter Insert for LCFH2
40um Mounted Pinhole
200um Mounted Pinhole
2" Mount for 1.5" Optic
700 mm Long Structural Rail
Locking Ball and Socket Mount, M6 x 1.0 threaded
60mm Cage-Compatible Dichroic Filter Mount
SM1 Kinematic Pitch/Yaw Ø11mm Collimator Adapter
SM05 Rotating Lens Tube, 1.0" Long
Metric 60mm Slip Plate Positioner
Flat Platform for Post Clamping Mount, M6 Threaded, Metric
66mm Universal Cylindrical Lens holder
30mm to 16mm Cage Adapter Plate
M8 to RMS Microscope Objective Adapter Ext. Tube
100mm Optic Holder
SM2 Lens Tube 2" Long Extension
45 Degree Mirror Mount For 1/2" Optics
Mini Series Clamping Fork Universal Fork
C-Mount 30mm Metric Cage Plate
XT66 single profile, 1000mm
150mm Metric Post Holder
Metric Right Angle Post Clamp for Ø25mm Post
16mm Quick Release Cage Mount
10W, Ø25mm Ring Heater with 10kΩ Thermistor
Rail Carrier, Perpendicular Dovetail
Rod Adapter for Ø4mm SR Rods, 4 Pack
Lens mounting ring for 1" dia optic #8-32 mounting
Metric 45 Degree Post Clamp, 5 pack
TNUT W/ M6 TAP, 10 per pack
30mm Lens Tube, 1"
Ø12mm to Ø1/2" Barrel Adapter
TR Series Alignment Key

Amb el suport de:

Rail Carrier, Extended 25mm x 50mm
Mounting adapter thin 1/2" optics
Large Clamping Fork w/ M6 x 1.0 captive screw, 5 pack
Precision Screwdriver Set, 7 piece
Unmounted Zero Aperture Iris, 25.0mm max. Aper.
Ball driver kit/ 6 tools
2 x 2 Blank Kinematic Mount
Shorter Spanner Wrench For SM1RR, 1" Long
SM2 Lens Tube 1" Long Extension
60mm Alignment Plate w/ 1mm Pinhole and Crosshair
1125mm Structural Rail
100mm Metric Post Holder
Mounting Post Shims, 20 mm
Mounting Adapter for Mounting 1" Optic in a 2" Mou
M6-1.0 to M4-0.7 Thread Adapter
XT95 Mounting Plate
SM05 to FC Adapter
Magnetic base 175# pull with M6 mounting hole
Mounting Base, 50mm x 75mm x 10mm
Extension Rod 18"
Extension Rod 10"
Mounting Base, 25mm x 75mm x 10mm Pack of 5
3 Way Cube
1/2" Dia . x 3" Length: Pack of 5 Post
Adjustable Lens Mount For Optic 19mm to 57mm
30mm Cage Support to XT66 Rail Adapter
90 Degree "T" Extention
30mm Cage Plate for 5.6mm Laser Diode, Metric
Telescoping Inspection Mirror
SM05 Lens Tube Sleeve, 1.5" Long
Outer ring for LM1-A/M & AM/M
Bellows for SM1 lens tube
11-Piece Color-Coded Hex Key Set, Imperial
SM1 Int to RMS Ext Adapter
Metric Rotating Plate
Metric Prism Mount
Metric Swivel Post Clamp
1674-001 Extension Rod 8 inch
SM2 Lens Tube Clamp
450 mm Long Structural Rail

Amb el suport de:

SM1 Ext to M32 Int Adapter
RMS Mount For C170TM
Mounting Post Shims, 10mm
2 Inch 45 Degree Fixed Mirror Mount
SM2 Series Lens Tube Cube
60.0mm CAGE PLATE, 6.0mm THICK
M6 X 1.0 Stainless Steel Cap Screw 20mm Long Pack of (25)
Metric Pair of Microscope Slide Spring Clamps
XE25 Enclosure Hinge
Post End Clamp 0.5 inch
Metric C6W Platform Adapter Kit
Mounting Post Shims, 5mm
Metric Post Mounted Stop
Metric Adjustable Plate Clamp
Nested 1" lens holder inner ring
Stackable mount 2" retaining ring
SM1 Lens Tube 1" Long Extension
SM2 External thread to Ø2" Adapter
RMS Int to M25-0.75 Ext Adapter
13034-001 1/2" Fixed mirror
Unmounted Standard Iris, 8.0mm max. Aper
Filter holder for 2" optic, stackable
Spanner Wrench with Clear Aperture for SM30 Retaining Rings
M26 INT to SM1 EXT Adpater
37.7mm dia. Mounting Post x 25mm
Adapter M4 to M3
M6 X 1.0 Stainless Steel Cap Screw 10mm Long Pack of (25)
Adapter, Internal C-Mount Threads
Large Metric V-Clamp with PM4, 2.5in Long
30mm Lens Tube, 3"
Metric, 2" Diameter Slip Ring
XT66 Rail Nudger
Thick SM2 60mm Cage Plate
135 Degree Metric Post Clamp
Metric Cage Plate to TR Post Bracket, 20mm Spacing
RS Series Laminated Post Spacer 1mm thick, Pack of 5
UV Curing Optical Adhesives
2" Mini Series Post Holder with ¼-20 [M6] Slot
Metric 25mm Dia. Riser Post, 12mm
Devcon 5 Minute Epoxy 25ml

Amb el suport de:

Ball driver for M6 socket screws-extra long
SM1 Lens Tube 3" Long Extension
SM1 Rotating Lens Tube, 1.5" Long
SM05 Lens Tube, 2.5in Extension
20mm Metric Post Holder
SM05 Lens Tube 2" Long Extension
610mm SM1 Series Non-flammable Lens Tube Cover
75mm Metric Post Holder
Metric Mini Series Swivel Post Clamp Adapter
30mm Lens Tube, 1/2"
RS Series Spacer, 7mm
7 Degree 41 Minutes Angled Wedge
4mm Compact Extension Rod, 4.0", Pack of 4
SM1 Threaded Delrin Mount for 9mm Laser Diode
SM2 Retaining Ring, 5 pack
RS Series Spacer, 6mm
Right Angle Bracket w/Counterbored Slots, Holes & M4 Tap
Lens mounting ring for 0.5" dia optic
1" Optic Mount for 30mm Cage Cube
Dual filter holder 8mm x 12.7mm x 30mm
Ball driver for M6 socket screws
M4 to M3 Thread Adapter
4mm Compact Extension Rod, 3.0" Pack of 4
SM05 Threaded Delrin Mount for TO-46 Laser Diode
60mm Cube Clamp
SM1 Off Axis Parabolic Adapter
Black Flocked Paper 30 inch x 30 inch
0° Angle Clamp for Ø1/2in post , 5mm hex
3/8 inch, 9mm Spanner Wrench
05 Optic Retaining Ring
Reversible Spanner Blade Set
Black masking tape 1"
1/2 inch Variable Zoom Lens Tube
1.3mm Balldriver
Dual Card Holder
Mounting Adapter for 08mm Modules to SM1 Threads
XT66 Clamping Platform, 40mm Long
LMR1 Alignment Plate, 2"
M6 Pillar Post C-clamp
Adapter w/ External SM2 Threads and External C-MOUNT Thread

Amb el suport de:

SM2 EXT to RMS INT Adapter
Post : 12.7mm Dia . 75mm Long
Alignment Plate with 5mm Pinhole
SM2 Retaining Ring, 5mm Thick
SM1 1" Lens Spacer
4mm Compact Extension Rod, 1.5", Pack of 4
RS Series Spacer, 8mm
SM05 Series 5.6mm Laser Diode Mount
Lens mount for 50.8mm optic
Rotatable Cover Plate
M6 to M3 Thread Adapter
SM05 Off Axis Parabolic Adapter
SM1 Isolator Adapter
Pack of 10, #6-32 x 1/8" Nylon Tip Set Screw
Spanner Wrench for SM05 Adapters
SM1 Lens Tube 1/2" Long Extension
CR1/M Adapter Plate
4mm Compact Extension Rod, 1.0", Pack of 4
0.050 Hex Key Thumb Screw
Metric 45deg Post Clamp
SM1 to 6mm Lens Cell Adapter
SM1 Aspheric Lens Cell Adapter
Post: 12.7mm Dia . 100mm Long
Horizontal Slide Mounting Base
4mm Compact Extension Rod, .5", Pack of 4
M3x0.5-3mm Long Nylon tipped set screw, Pack of 10
¼" Washer 316 SS, Pack of (25), Vacuum Compatible
Fiber Optic Storage Reel
RMS Mount for C110TM & C220TM
RMS Int. to M27 Ext. Thread Adapter
10mm Lens Adpater
SM05 Externally Threaded Coupler, 1" Long
TR Series Spacer, 6mm, Pack of 5
SM1 Int to M25-0.75 Ext Adapter
SM05 to 6mm Lens Cell Adapter
SM1 DUST COVER 24" LONG
XT66 Double Dovetail Clamp, 40mm long
Metric 25mm Dia. Riser Post, 25mm
M25.5x0.5 Int to SM1 Exit Adapter
SM05 External to C-Mount Adapter

Amb el suport de:

Tapped Pedestal Base Adapter, 1/4-20 Thread
8 Degree Angle Block, Tapped
16 Degree Angle Block, Tapped
24 Degree Angle Block, Tapped
30 Degree Angle Block, Tapped
1/4-20 Stainless Steel Washer Pack of (100)
Female SM1 Quick Release Adapter Half
1" Adapter for 10mm Optic
1" Adapter for 13mm Optic
Pedestal Post Position Retainer
SM05 Coupler External Threads
SPW210, 10mm Spanner Wrench
Lens Mount with Retaining Ring for Ø9 mm Optics, 8-32 Tap
TR Series Spacer, 2mm, Pack of 5
TR Series Spacer, 3mm, Pack of 5
TR Series Spacer, 1mm, Pack of 5
X-Axis Dovetail, 50mm Length
M6 X 1.0 Stainless Steel Set Screw 12mm Long Pack of (25)
Lens Mount with Retaining Ring for Ø6 mm Optics, 8-32 Tap
Center Mount 3 Inch Post Joist Metric
Black masking tape 2"
Spanner Wrench Tool for use with SM05, SM1 and C-Mount loc
12893-001 , Spanner Wrench for a 8mm Housing
Magnetic Measuring Tape
8mm Lens Adapter for LMR05
6mm Lens Adapter for LMR05
Spaner Wrench for a 6mm Optics Housing
Compact Cage Plate with SM05 Thread
50mm Metric Post Holder
1.5" SM1 Lens Tube Spacer
30mm Cage Spacer Rod
12mm Spanner Wrench
Post: 12.7mm Dia . 150mm Long
1/2" Stackable Lens Tube
1" post holder with spring-loaded thumbscrews
Plastic Objective Cap, RMS threads
Locking Nut 1.035-40
M3x0.5 6mm Long Nylon Tip Set Screw, Pack of 10
16mm Alignment Plate w/ 1mm Pinhole and Crosshair
M6x1.0 Stainless Steel Cap Screw, 6mm Long; Pack of 25

Amb el suport de:

115 mm Long Base Plate
SM2 DUST COVER 24" LONG
Spring Loaded 5mm Hex Locking Thumbscrew Pack of 5
Red Vinyl Tape, 1/2"
Yellow Vinyl Tape, 1/2"
Green Vinyl Tape, 1/2"
M4-0.7 External to #8-32 External Adapter
M4 X 0.7 Stainless Steel Set Screw 12mm Long Pack of (50)
#8-32 x 1/8" Nylon Set Screw, 10 pack
Balldriver 3/16 for 1/4-20 socket head screw
Post : 12.7mm Dia . 50mm Long
Plastic Objective Case, 2" diameter, 2.5" long
Metric Quick Release Clamp for C1500 Series
3mm Balldriver
9/64" Balldriver
1/8" BALL END SCRDRV YELLOW HANDLE
2mm Balldriver
3" post holder with spring-loaded thumbscrew
Connector Caddy
1.5 mm Balldriver
M4 X 0.7 Stainless Steel Cap Screw 20mm Long Pack of (50)
M4 X 0.7 Stainless Steel Cap Screw 12mm Long Pack of (50)
Mini Series Posts, 6mm, 50mm
M4 X 0.7 Stainless Steel Cap Screw 6mm Long Pack of (50)
Mounting Base, 25mm x 75mm x 10mm
Lens Spacer Ring, 0.015 Thick, 10 Pack
Mounting Base, 25mm x 10mm
5/32" Balldriver
2.5mm Balldriver
7/64" Balldriver
3/32" Balldriver
1/16" Balldriver
10 Pack of 0.05" Hex Keys
13489-001, 4mm Compact Extension Rod, 6"
4mm Compact Extension Rod, 2.0", Pack of 4
Curved Forceps solid stainless steel
4-40 Hardware Kit for Mini Series
Forceps solid stainless steel
1" XYZ Metric 60mm Cage Translator
Tunable laser (C-Band)

Amb el suport de:

4-Channel Laser Source, USB Interface, TEC Stabilized
PM100D Power Energy Meter w. Graphics Display
Single Frequency Laser 1550 nm, PM Fiber, FC/APC
Single Frequency Laser 1550 nm, SM Fiber, FC/APC
PDB435C-AC; fast monitor ports, low distortion, 350MHz, InGaAs
Benchtop Temperature Controller, ± 2 A / 12 W
10 GHz Phase Modulator without Polarizer, FC/PC Connectors
Optical Chopper System
PDB435C; fast monitor ports, low distortion, 350MHz, InGaAs
Benchtop LD Current Controller, ± 200 mA HV
CMOS Camera, 1280x1024, Monochrome, USB2.0
Compact Scientific 8.9MP Mono Camera, USB3.0
LED driver in a Tcube 1200mA
Laser Safety Glasses, 75% Visible Light
Compact QTH Light Source, Metric
Silicon Power Head, 400-1100nm, 500mW
Compact Spectrometer 500-1000 nm, metric
Mounted VIS C Linear Polarizer, 25.0mm OD
PDB450C-AC; fast monitor ports
Fiber Coupled LED @ warm white
PDB450A-AC; fast monitor ports
Ge, 800-1800 nm, 590 kHz BW, 7.1 mm ² , Switchable Gain
Laser Diode Mount with Integrated Temperature Control
Laser Safety Glasses, Clear Lenses, 75% Visible Light Trans
Universal 14 Pin Butterfly LD Mount
Liquid Crystal Controller 0-25VAC very Low DC offset
InGaAs, 900-2600 nm, 25 ns Rise Time, 0.8 mm ²
Avalanche Detector, adj. Gain, 10 MHz, 400-1000nm
Standard Photodiode Germanium Power Head, 700-1800nm, 40mW
Si, 200-1100 nm, 150 MHz BW, 0.8mm ² , Fixed Gain
InGaAs, 900-1700 nm, 13 MHz BW, 0.8 mm ² , Switchable Gain
Avalanche Detector, adj. Gain, 400 MHz, 400-1000nm, M
CMOS Camera, global shutter, 1280x1024, Color, USB2.0
General Purpose Temperature Controller w/European line cord
Electronic controlled 1x2 switch module 1310&1550nm
Si-Sensor Power Meter with Bluetooth and USB Interface
Benchtop LD Current Controller, ± 20 mA
Avalanche Detector, 400-1000nm, M4
Large Area Ampl. Photo Detector, Si, Fixed Gain, Metric
Large Area Ampl. Photo Detector, Si, Fixed Gain

Amb el suport de:

Silicon Power Head, 400-1100nm, 50mW
1" Teflon-Coated Diaphragm Optical Beam Shutter w/Controller
High Intensity Fiber Coupled Light Source
Viewing Card for 400-640nm & 800-1700nm
USB Power and Energy Meter Interface
High Sensitive Thermal Power Head, 10μW-1W, BB
Shutter Controller
Slim Germanium Power Head, 700-1800nm, 5mW/500mW
CMOS Camera, 1280x1024, Color, USB2.0
976nm, 300mW, 14-Pin Cooled Butterfly-Packaged Laser
Si, 350-1100 nm, 12 MHz BW, 13 mm ² , Switchable Gain
Ge, 800-1800 nm, 650 ns Rise Time, 7.1 mm ²
Laser Safety Glasses, 11% Visible Light
1" Beam Shutter - Metric, RA, 24065
USB Power Meter, Silicon Sensor 50mW
Dual Band Si/InGaAs Detector, 4 μs Rise Time, 400 - 1700 nm
InGaAs Detector, 800nm to 1700nm, 80um, Window, Metric
negative 18mmx18mm resolution and distortion target
InGaAs Fiber Power Head, 800-1700nm, 20mW
Standard enclosure, 200 x 300 x 105 mm
IR Viewing Card 700-1400nm, Orange / 625nm
Slim Silicon Power Head, 400-1100nm, 5mW/500mW
Viewing Card, 790-840, 870-1070, 1500-1590nm
V450A
Fiber Coupled LED @ 740nm
Amplified PbSe Photodetector, 2x2mm, 1.5-4.8 m
24" x 36" Adhesive Mat With 30 sheets
Fiber Coupled LED @ 810nm
Silicon Power Head, 200-1100nm, 50mW
Temperature and Humidity USB Sensor Probe
Fiber coupled LED @ 415 nm
EF500 DC Block
Fiber coupled LED @ 455 nm
Fiber Coupled LED @ 595nm
Fiber Coupled LED @ 617nm
Fiber Coupled LED @ 625nm
Si, 320-1100 nm, 11 MHz BW, 75.4 mm ² , Switchable Gain
Si, 350-1100 nm, 14 ns Rise Time, 13 mm ²
SM05 Mounted Ge-Photodiode, A-Type, 800 1800nm
FC Fiber Adapter with SM1 for Power Meter Sensors

Amb el suport de:

Laser Glasses, 190-400nm, 808-1090nm
Red Enclosure for Electronics, 200 mm x 300 mm x 96 mm
5VDC Power Supply, 330mA, Regulated w/European line cord
1mm InGaAs PHOTODIODE
Laser Glasses, 190-400nm OD5+, 625-850nm OD4+
Si, 320-1100 nm, 35 ns Rise Time, 75.4 mm ²
Foil Heater with 10K NTC Thermistor
2000um confocal annular precision pinhole
1000um confocal annular precision pinhole
Laser Glasses, 180-532nm
Cable, SMA(M)-GPO(F), 3"
Silicon Fiber Power Head, 350-1100nm, 5mW
Si Detector, 400-1100nm, 250um, FC Coupled, Metric
Collimated Laser Diode Module, 635 nm, 1.2 mW, Round Beam
Adjustable Collimation Optic for VIS - 2 Zoll
TC200, 10ft Hirose Cable
Current Amplifier, DC-100kHz, 100kV/A
Fiber Connector Cleaner 20ft Universal
SM1-Threaded VIS and IR Alignment Disk 400-640, 800-1700nm
Adjustable Collimation Optic without lens
635nm, 5mW Hitachi Diode
Power Supply, ± 12 VDC, 6W, 115/230 VAC
Focus adjustable laser diode module, 670nm, 4.5 mW
Mounted LED @ 940nm
Negative USAF1951 wheel pattern
Mounted LED @ 595nm
Laser Safety Glasses, Teal Lenses, 35
SM05 Mounted InGaAs-Photodiode, A-Type, 900-1700 nm
USAF1951 wheel pattern positive
15W Resistive Cartridge Heater
Laser Glasses, 190nm-534nm, 850-1070nm
Tunable Laser Kit heater
Mounted LED @ 680 nm
240 kHz Low Pass Electronic Filter, BNC coaxial
500 kHz Low Pass Electronic Filter, BNC coaxial
Mounted LED @ cold White 6500K
Laser Glasses, 180-450nm OD5+, 820-1720nm OD3+
30 mm Cage System Alignment Plate with IR Disk
Collimation Optics Adapter SM2 to Olympus BX/IX for VIS
SLS201 collimator with quick release

Amb el suport de:

785 nm, 90 mW, Ø5.6 mm, C Pin Code, Laser Diode
Mounted LED @ Warm White 3000K
QTH 10W LAMP/METRIC
Fixed Terminator Kit, set of 8 values
4.5mW, 532nm, collimated DPSS laser diode module
Laser Safety Glasses, Dark Blue Lense
Collimated DPSS laser Module, 532nm, 0.8mW, Round Beam
+12V DET Power Adapter
Laser Safety Glasses, Blue Lenses, 3
Base card of mid IR detector card
Mounted LED @ Neutral White 4900K
20 kHz Low Pass Filter, In-Line BNC
LD Controller Cable with 9 pin D-Sub Conn
Pigtailed Silicon Photodiode 625nm GRIN
MTDEVAL1
Cable, SMA(M)-SMA(M), 36"
EF599 DC BLock 60/120 Hz rejection
MLD Series Evaluation Board
Connector, M8, 4 pole, flying lead, 0.5M length
2 Slot Blade for Optical Chopper, 4Hz - 200Hz
InGaAs Photodiode 800-2600nm
Silicon PIN photodiode with 10ns risetime
Alignment Disk, 790-840, 870-1070nm, 1500-1590nm
Drop-in IR Viewing/Alignment Disk, 1"
Replacement Cleaning Media Refill - 20ft
8oz One-touch Pump Dispenser
3200K Replacement Bulb for OSL2 and OSL1, JCR 21V-150 10H/5
APC Laser Driver, 0-250mA
Temperature Probe for TSP01
19W Metal Ceramics Heater, Ring Shape, External diameter: 23
10-Function Digital MultiMeter
10 Slot Blade for Optical Chopper, 20Hz to 1kHz
Cable, SMA(M)-SMA(M), 6"
6 AMP Thermoelectric Cooler
Static Control Table Mat 2' x 4' x 3/32" ESD
SM1 thread adapter for S130 series power sensors
405 nm, 40 mW, Ø5.6 mm, B Pin code, Sanyo Diode
SM1-Threaded IR Viewing/Alignment Disk 790-840,870-1070
SM05 Int to SM1 Ext Adapter with Knurled Edge
Diode Laser Socket 3 Pin

Amb el suport de:

4.5 MHz Low Pass Electronic Filter, BNC coaxial
EF501 Electrical Filter, 10 MHz
SMA Coaxial Cable, SMA Male to SMA Male, 6" (152 mm)
SM05 Mounted Si-Photodiode, A-Type, 350-1100nm
10000 mAh Battery Pack and USB to Phono cable for CPS lasers
635nm, 15mW, Hitachi Laser Diode
10 kHz High Pass Filter, In-Line, BNC
50 kHz Low Pass Filter, BNC in-line
EF505 130 kHz Hi P, BNC Coax
2.5A TEC Element, ROHS
SMA Female to BNC Male Adapter
SM05 Mounted Si-Photodiode, A-Type, 320-1100nm
SMA Coaxial Cable, SMA Male to SMA Male, 24" (609 mm)
3500 ul Macro Quartz Cuvette, pack in 2
SM05 End Cap Coated w. 1mm Sphere Material
FGA015
405 nm, 20 mW, Ø5.6 mm, B Pin Code Laser Diode
ESD Protection for LT-Series Laser Tubes
1" x 48" Thermally Conductive Double-sided Tape
FDS015
690nm, 35mW Hitachi Laser Diode
4/7 Slot, 50% Duty Cycle Blade for Optical Chopper
60 Slot Blade for Optical Chopper, 120Hz - 6kHz
780nm, 10mW Laser Diode
5/7 Slot, 50% Duty Cycle Blade for Optical Chopper
24W Metal Ceramics Heater Square Shape, 20mm*20mm
14-Slot Cable Rack
72" OEM PDA Power Cable
OEM Temperature Controller, on Daughterboard, Thermistor
785nm, 5 mW, Ø5.6, A Pin Code Diode
FC Fiber Adapter for PM20 Series
SMA Male Straight to BNC Male Straight Cable, 6"
658nm, 40mW Laser Diode
Universal LED Mount for TO-18 and T1-3/4
SMA Male to BNC Female Adapter
MLD203CLN on Adapter for Evaluation Board
Diode Laser Socket, 5.6mm Lasers, Rohs
100 Ohm Platinum Thermistor
Extrusion Clamp Mount, 1.00in
Diode Laser Socket 4 Pin

Amb el suport de:

White High Intensity LED (5pk)
Solder Tail Photodiode Socket for TO-46 and TO-18 Diodes
72" USB Extension with A plug/A jack
Pass Through Photodiode Socket for TO-46 and TO-18 Diodes
PM100A Power Meter w. Analog/Digital Display
Benchtop LD and Temp. Controller 1A LDC 8A TEC
3 Port Fiber Circulator w/FC APC Connectors
Patch Cable, PM, FC/APC, 405 nm, Panda Style, 1 m
1x2 200 um coupler MM 50:50 FC/PC
50 mW 1625nm Fabry-Perot Pigtail Laser in a TO-56 Package
Inline Faraday Rotator Mirror for 1550 nm, FC/APC
PM, FC/APC, 620-850nm, FT030-BLUE, 10m, Ø125µm, 0.12, Panda
PM, FC/APC, 770-1100nm, FT030-BLUE, 5m, Ø125µm, 0.12, Panda
SMF-28-J9 Custom Patchcord MUC
FC to FC Mating Sleeve, Narrow Precision Key (2.0mm)
Adjustable FC/PC or APC Collimator, 1050-1620 nm, EFL 4.6mm
High Precision Fiber Cleaver, switchable blade position
630HP Custom Patchcord MUC
Rack Box Chassis with Blank Front Panel, M6 Breadboard
PM, FC/APC, 770-1100nm, 10m, Ø125µm, 0.12, Panda
780HP Custom Patchcord MUC
Fiber Polarization Beam Combiner 1550 ±40nm SM output FC/APC
Fiber Polarization Controller w/ Large Paddles, No Fiber
Custom WDM 780/840 nm
Ø1" to FC/APC Fiber Bulkhead Adapter
SM1 to FC/APC Fiber Bulkhead Adapter
PM, FC/APC, 620-850nm, FT030-BLUE, 2m, Ø125µm, 0.12, Panda
Passive Component Fiber Tray
Ø50 µm, 0.22 NA, SMA-SMA Fiber Patch Cable, 1 Meter
Variable Optical Attenuator for FC/PC Multimode Patch Cables
FC/APC to FC/APC Mating Sleeve, Narrow Key (2.0mm), SquareFl
FT200EMT Custom Patchcord MUC
PM, FC/APC, 405-532nm, FT030-BLUE, 2m, Ø125µm, 0.12, Panda
GIF625 Custom Patchcord MUC
Fiber Optic Circulator, 1050- 1070 nm, SMF, FC/APC
2x2 Broadband Fiber Coupler, 630 ± 50 nm, 90:10 FC/APC
S405-XP Custom Patchcord MUC
2x2 Broadband Fiber Coupler, 630 ± 50 nm, 50:50 FC/APC
Fiber Polarization Beam Combiner 1064 ±20nm SM output FC/APC
Custom Fanout Fiber Bundle, 0.22 NA, Ø50 µm Core

Amb el suport de:

PM Variable Attenuator, 1310/1550 nm ,50dB, FC/APC
Custom Fan Out Bundle SM Fiber 600-770nm, Ø125 µm Cladding
Hollow Core PCF, 1570nm, 20µm core
2x2 PM Coupler, 780 ± 15nm, 50:50 Split, FC/APC
2x2 PM Coupler, 1550 ± 15nm, 99:1 Split, FC/APC
Fiber Polarization Controller w/ Large Paddles, FC/PC
2x2 PM Coupler, 780 ± 15nm, 99:1 Split, FC/APC
2x2 PM Coupler, 1550 ± 15nm, 50:50 Split, FC/APC
2.5mm FC/PC, ST, and SC Fiber Bulkhead and Connector Cleaner
PM, FC/PC to FC/APC, 1440-1620nm, 2m, Ø125µm, 0.125
FiberCable, MM, Silica, FC/PC, 62.5µm, .275NA, 3M, 800-1600
Patch Cable, PM, FC/APC, 405 nm, Panda Style, 10 m
PM Fiber Isolator, 1550 nm, 300 mW, Pol. Dep., FC/APC
Hollow Core PCF, 2000 nm, 14.5 µm Core
2 Color Combiner 633/473nm FC/PC
PM, FC/PC to FC/APC, 460-700nm, 1m, Ø125µm, 0.12, Panda
SM1-Threaded Adapter for Ø9.5 mm Cylindrical Components
1x2 Broadband Fiber Coupler, 470 ± 40 nm, 50:50 FC/PC
Fixed Fiber Optic Attenuator, 630-780nm, <=2dB, FC/PC
Graphite Filament Assembly for up to 1.8mm
FC/APC to FC/APC Mating Sleeve, Narrow Key (2.0mm), D-Hole
Fiber In-Fiber Polarizer, 1550nm, PM/PM Pigtailed, FC/PC
1x2 MM Coupler, 50:50 Split, 0.22 NA, High-OH, Ø50µm, FC/PC
Patch Cable, SM, FC/PC, 780-970nm, FT030-Y, 5m, Ø125µm, 0.13
SM Patch Cable, 980–1650 nm, FC/APC, Ø900 µm Jacket, 2 m
PM, FC/PC, 460-700nm, FT030-BLUE, 5m, Ø125µm, 0.12, Panda
2x2 Broadband Fiber Coupler, 1430 ± 100 nm, 50:50 FC/PC
SM, FC/APC, 488-633nm, FT030-Y, 2m, Ø125µm, 0.10-0.14
SM600 Custom Patchcord MUC
FC/PC to FC/PC Mating Sleeve, Wide Key (2.2mm), SquareFlange
FC/PC to FC/PC Mating Sleeve, Wide Key (2.2mm), D-Hole
Low IL SM, FC/APC, 488-633nm, 1m, Ø125µm, 0.10-0.14
PM, ESM Large-Mode-Area Photonic Crystal Fiber, Ø15 µm Core
Linear Bundle, 1 X 7 Ø200/220 Fiber, Low OH, SMA, L=2m
2x2 Broadband Fiber Coupler, 805 ± 75 nm, 99:1 FC/PC
Variable Attenuator,1310 /1550 nm,50dB, In-Line, FC/PC
Ruby DualScribe Fiber Optic Scribe
Ø105 µm, 0.22 NA, SMA-SMA Fiber Patch Cable, 5 Meters
Adjustable FC/PC or APC Collimator, 1050-1700 nm, EFL 2.0mm
FC/APC to FC/APC 4-Fold L-Bracket Mating Sleeve, Narrow Key

Amb el suport de:

SM, FC/PC to FC/APC, 488-633nm, FT030-Y, 1m, Ø125µm
FG200LEA Custom Patchcord Muc
Fiber Cable, MM, Silica, SMA-SMA, Ø105 µm, 0.1 NA, 2 m,
AR Coated, PM, FC/PC, 1440-1625nm, 2m, Ø125µm, 0.125
Optic Tweezer w/ SS Body & Carbon-Fiber Tips
PM, FC/APC, 460-700nm, FT030-BLUE, 2m, Ø125µm, 0.12, Panda
PM630-HP Custom Patch Cord
PM, FC/PC, 460-700nm, FT030-BLUE, 2m, Ø125µm, 0.12, Panda
Patch Cable, PM, FC/PC to FC/APC, 405 nm, PANDA, 1 m
PM, FC/APC, 460-700nm, FT030-BLUE, 1m, Ø125µm, 0.12, Panda
FC to FC Single L-Bracket Mating Sleeve, Narrow Precision Key
50 µm, 0.22 NA, FC/PC-FC/PC Fiber Patch Cable, 1 Meter
Rack Box SMA/SMA Electrical Feed-Thru Panel
Fiber Collimator, High NA, MM, achromat 350-700nm, FC/PC
1x2 Narrowband Coupler, 632 ± 15 nm, 50:50 Split, FC/PC
PM, FC/APC, 970-1550nm, FT030-BLUE, 2m, Ø125µm, 0.12, Panda
Ø400 µm, 0.39 NA, SMA-SMA Fiber Patch Cable, 2 Meters
PM, FC/APC, 620-850nm, FT030-BLUE, 1m, Ø125µm, 0.12, Panda
SM, FC/APC, 488-633 nm, FT030-Y, 1m, Ø125µm, 0.10-0.14
ST Polishing Disc
Rack Box 1 width slot Blank Panel
SM, FC/APC, 1260-1625nm, FT030-Y, 1m, Ø125µm, 0.14
FC/PC TO SMA Fiber Optic Mating Sleeve
Ø400 µm, 0.39 NA, SMA-SMA Fiber Patch Cable, 1 Meter
Connector Cleaning Sticks
Patch Cable, PM, FC/PC to FC/APC, 1550 nm, Panda, 1 m
PM, FC/APC, 970-1550nm, FT030-BLUE, 1m, Ø125µm, 0.12, Panda
FC/APC to FC/APC Single L-Bracket Mating Sleeve, Narrow Key
PM, FC/APC, 770-1100nm, FT030-BLUE, 1m, Ø125µm, 0.12, Panda
50 µm, 0.22 NA, FC/PC-FC/PC Fiber Patch Cable, 5 Meter
6" x 6" Diamond Lapping (Polishing) Sheet, 1 µm (5 Sheets)
Splice Protector Sleeve 60mm (25/pkg)
Rack Box AC Power Entry Module Panel
Precision Optical Cleaner
Multimode Fiber, 0.50 NA, High OH, 1500 um Core
SM450 Custom Patchcord MUC
125.5µm FC/PC SM PM Adjustable Key Ceramic Ferrule for BFT
ESM Large Mode Area Photonic Crystal Fiber, Ø12 µm Core
SM, FC/PC, 320-430nm, FT030-Y, 1m, Ø125µm, 0.12-0.14
460HP Custom Patchcord MUC

Amb el suport de:

Low IL SM, FC/PC to FC/APC, 488-633nm, 1m, Ø125µm, 0.10-0.14
630HP - Custom Patch Cord
PM , FC/PC, 1440-1625nm, FT030-BLUE, 1m, Ø125µm, 0.13, Panda
50 µm, 0.22 NA, FC/PC-FC/PC Fiber Patch Cable, 2 Meter
Lint-Free Wipes
Rack Box Cooling Fan Sub-Panel
SMF28 Custom Patchcord MUC
Patch Cable,SM, FC/APC, 780-970nm, FT030-Y, 5m,Ø125µm, 0.13
SM, FC/PC, 633-780nm, FT030-Y, 1m, Ø125µm, 0.10-0.14
Fixed Optical Attenuator, 10dB, FC/APC connector
Rack Box APC/APC Optical Fiber Sub-Panel
25 µm, 0.10 NA, FC/PC-FC/PC Fiber Patch Cable, 2 m
Ø600 µm, 0.50 NA, FC/PC to SMA Fiber Patch Cable, 2 m
SM, FC/PC, 1260-1625nm,FT030-Y, 1m, Ø125µm, 0.14
6" x 6" Diamond Lapping (Polishing) Sheet, 3 µm (5 Sheets)
6" x 6" Diamond Lapping (Polishing) Sheet, 30 µm (5 Sheets)
6" x 6" Diamond Lapping (Polishing) Sheet, 6 µm (5 Sheets)
Ø1000 µm, 0.39 NA, SMA-SMA Fiber Patch Cable, 2 Meters
SM, FC/APC, 633-780nm, FT030-Y, 2m, Ø125µm, 0.10-0.14
Ø600 µm, 0.39 NA, SMA-SMA Fiber Patch Cable, 2 Meters
SM, FC/PC, 400-532nm, FT030-Y, 5m, Ø125µm, 0.12-0.14
Fixed Optical Attenuator, 10dB, FC/PC connector
Fixed Optical Attenuator, 5dB, FC/PC connector
Fixed Optical Attenuator, 3dB, FC/PC connector
SMF-28 ULTRA, FC/PC to FC/APC, 1260-1625nm, 5m, Ø125µm, 0.14
SMF-28 ULTRA, FC/PC to FC/APC, 1260-1625nm, 2m, Ø125µm, 0.14
SM Patch Cable, 980–1650 nm, FC/APC, Ø900 µm Jacket, 1 m
Ø550 µm, 0.22 NA, SMA-SMA Fiber Patch Cable, 1 Meter
SMF-28 ULTRA, FC/PC to FC/APC, 1260-1625nm, 1m, Ø125µm, 0.14
Ø400 µm, 0.39 NA, FC/PC-FC/PC Fiber Patch Cable, 1 m
FC to FC Mating Sleeve, Wide Precision Key (2.2mm)
Fiber Cable, MM, Silica, FC/PC-SMA, Ø200 µm, 0.50 NA, 1 m,
Fiber to Fiber Adapter, SMA Adapter
SM, FC/APC, 1460-1620 nm, FT030-Y, 1m, Ø125µm, 0.13
Ø600 µm, 0.39 NA, SMA-SMA Fiber Patch Cable, 1 Meter
Fiberbench 1.5mm aperture alignment tool
Fiber Cable, MM, Ø200 µm, 0.39 NA, FC/PC to SMA, 2 Meters
Fiber Cable, MM, Ø200 µm, 0.39 NA, FC/PC to SMA, 1 Meter
2.5mm FC,SC Fiber Bulkhead 750 Cleaner
Kim Wipes, 280 Kimwipes per Box, 12 Boxes per Case

Amb el suport de:

Ø200 µm, 0.22 NA, SMA-SMA Fiber Patch Cable, 1 Meter
SM, FC/APC, 980- 1550 nm, FT030-Y, 2m, Ø125µm, 0.10-0.14
SM Patch Cable, 633 - 780 nm, FC/APC, Ø900 µm Jacket, 2 m
200 µm, 0.50 NA, FC/PC-FC/PC Fiber Patch Cable, 1 Meter
400 µm, 0.50 NA, FC/PC-FC/PC Fiber Patch Cable, 1 Meter
Fiber Cable, MM, Ø200 µm, 0.39 NA, FC/PC-FC/PC, 1 Meter
Fiberbench 2.5mm aperture alignment tool
6" x 6" Final Polishing Film Sheet (5 Sheets)
SM Patch Cable, 633 - 780 nm, FC/APC, Ø900 µm Jacket, 1 m
Fiber Cable, MM, Ø200 µm, 0.39 NA, FC/PC-FC/PC, 2 Meter
SM, FC/PC, 980-1550nm, FT030-Y, 5m, Ø125µm, 0.13-0.15
340µm SMA905 MM Stainless Ferrule for BFT
Hi-Temp Epoxy, 4g Packets, 10 per Pack
SM, FC/PC, 488-633nm, FT030-Y, 1m, Ø125µm, 0.10-0.14
Fiber Cable,MM,SMA,400µm,0.50,1m,400 - 2200 nm,FT030
105 µm, 0.22 NA, FC/PC-FC/PC Fiber Patch Cable, 2 Meter
Ø105 µm, 0.22 NA, SMA-SMA Fiber Patch Cable, 2 Meters
Ø105 µm, 0.22 NA, SMA-SMA Fiber Patch Cable, 1 Meter
APC Fiber Adapter with SM1 for Power Meter Sensors
SM, FC/APC, 1260-1625nm, FT030-Y, 5m, Ø125µm, 0.14
126µm FC/PC SM Ceramic Ferrule for BFT
3 hole Stripping Tool for Fiber Buffers and Jackets
Optical Fiber, Ø900µm Jacket, 100m Length, Ø125µm Cladding
Single L-Bracket mount for D-Hole FC Mating Sleeves
1" x 2" Ceramic Fiber Scribe, Pack of 5
Splice Protector Sleeve 40mm (25/pkg)
Singlemode Optical Fiber, 980nm
Ø2.75" CF Gasket, 1/4 Hard OFHC Copper, Pack of 10
Kapton Tape , 3/4" Wide x 36 yd Long
1/2" to FC/APC Fiber Bulkhead Adapter
Fiber Tip Disposal Unit
Dust Caps for FC connectors 25pack
Clean Out Wires (8 Pieces Per Vial)
Standard 10X Eye Loupe
Epoxy Mixing Kit
adjustable fiber stripper
Kevlar Cutting Shears
LC to LC Mating Sleeve
Metal Cap and Chain for SMA Mating Sleeves
Fiber Polishing Notes

Amb el suport de:

White Dust Caps for Ø1.25 mm Ferrules 25pack
1.818mm ID, GRIN/Ferrule Sleeve, 10mm Length
Rubber Gripper for Bare Fiber Optics
SM Patch Cable, 780 - 970 nm, FC/PC, Ø900 µm Jacket, 1 m
17.5cm +/- 2.5 cm long, no labels, just boots, FT900SM-BLUE
25mm Travel, Stepper Motorised Folded Actuator, 3/8" Barrel
2D Galvo System with metric accessories
NanoMax300 with Diff Drives, No Piezo
T CUBE LASER DIODE CONTROLLER
Side Actuated 1/4" Travel Translation Stage
CAGE XY FLEXURE ADJUSTMENT PLATE
Ø1" Motorized Rotation Stage (Metric), Controller and PSU
Motorized Cage Rotator - Metric
XYZ Differential Translation Stage
Pitch and Roll Tilt Platform with Thumbscrew Drives (M)
Four Position SM1 Slider Kit
Single Channel Open-Loop Piezo Controller
Rotating Breadboard - 450mm
50mm TravelMax Stage with Differential Drive
25mm Travel , Stepper Motorised Actuator, 3/8" Barrel
Metric XYZ Translation Stage (Includes PT102/M)
1" MOTORISED HIGH PRECISION ROTATIONAL MOUNT (METRIC)
Quadrant Detector Infrared Sensor Head
ELLIPTEC BI-POSITIONAL SLIDER
Metric Precision Rotation Platform
1" Motorised Filter Flipper - Metric
Metric 1/2" Translator Stage
Piezoelectric Actuator
Metric Mini Translation Stage
50mm Dovetail Translation Stage
Translation Stage Kit - Metric
T-CUBE DC PSU (2-WAY);±15 V/5 V Power Supply Unit for 2 TCub
1/2" (12mm) XYZ Dovetail Translation Stage
1D Galvo Cage System Mount
Bi-positional Slider Kit
Four Position SM1 Slider
Metric Breadboard Adapter
5x5x3mm 150V piezo chip with wire
K-Cube Power Supply
Post Mount Adapter

Amb el suport de:

Rotation Platform
1" Manual Rotation Stage, Metric
RollerBlock Breadboard Pattern Adapter Plate
Z Bracket for Metric LTS300 Stages
Vert Mount Bracket For NRT Series
Goniometer with 1 inch Virtual Point
DT12 Rotation Adapter (Metric)
5.2x7.1x20.1mm piezo stack 75V with one spherical end
1/2 inch Differential Adjuster
TST101 to ZST 1m Extension Cable
Identification Cable Tie Pack (100 off)
M2.5-0.20mm x 20mm Extremely Fine Hex Adjuster
Threaded Bushing M2.5 - 0.20 x .276
50x50mm Black Trunking (1m)
OD 8mm ID 7mm Length 10mm tube with wires
RBB Accessory SM1/M
Piezoelectric Actuator
DT12 Adapter Plate
Base Plate for DT12 Stages (Metric)
M2.5-0.20mm x 12mm Extremely Fine Hex Adjuster
Hi Density Dtype straight thro Male to Female extender cable
M4 x 0.25 BUSHING VACUUM COMPATIBLE
Piezo Actuator Tip, Flat End
M6 / 1/4" Cable Ties Bases (250 off)
Angle Plate for DT12 Stages
Fine Hex Adjuster, M4 x 0.25, 8 mm Long
Slit Harness Wrap 5m + Tool
Hook And Loop Reel Black (5m)
MS-Series Angle Bracket
PR01/M Adapter Plate
Grease Kit for Z8 Actuators
Mounting barrel adapter, Ø3/8in to 1/4-100
Mounting barrel adapter, Ø3/8in to M6 x 0.25
Piezo Actuator Tip, Threaded M4
M3-0.20 Removable Adjuster Knob
MS-Series Base Plate
Threaded Bushing 1/4 - 80 x .57
Galvo Mount Tip-Tilt Platform Adapter
Releasable Cable Ties (100 off)
M3-0.20mm x 8mm Extremely Fine Hex Adjuster

Amb el suport de:

Threaded Bushing M3 - 0.20 x .276
1/4" ultra fine adjustment screw
1-1/4" ultra fine adjustment screw
1" ultra fine adjustment screw
1/4-100 x 2 Extremely Fine Hex Adjuster
1/4-100 x 1-1/2 Extremely Fine Hex Adjuster
Fine Hex Adjuster, M6 x 0.25, 25 mm Long
Fine Hex Adjuster, M6 x 0.25, 20 mm Long
Brushless DC Rotary Stage - Metric
POWER CORD EUROPE - Value for customs purposes only \$1.00
VER05 EUR Adapter Plug - Value for Customs Only \$1.00
Aluminium Breadboard 450 x 600 x 12.7mm
600 x 900 x 60 mm Metric Breadboard
6283-001 Rev E, Breadboard 600 mm x 600 mm x 12.7 mm
Aluminium Breadboard, 300 mm x 450 mm x 12.7 mm, M6 taps
600 x 600 x 60 mm Metric Breadboard
Aluminium Breadboard 450 x 450 x 12.7mm M6/25mm
Aluminum Breadboard 300 mm x 300 mm x 12.7 mm, M6 taps
Optical Breadboard - 600 x 600 x 25mm
Temperature-Controlled Breadboard, metric version
Sorbothane Feet, Ø27mm Female M6 Thread
Aluminium Breadboard 150mm x 300mm, M6 Taps
Aluminum Breadboard, 300 mm x 600 mm x 12.7 mm, M6 Taps
Standard Duty Passive Upgrade Kit
Aluminium Breadboard 750 x 450 x 12.7mm M6/25mm
Optical Breadboard - 300 x 300 x 25mm
LIGHT DISPERSIVE SHIELD 12" x 12" (304.8 mm x 304.8 mm)
0689-001 REV F Breadboard 150 mm x 150 mm x 12.7 mm
Magnetic Light Dispersive Shield Metric
Aluminum Breadboard, 300 mm x 900 mm x 12.7 mm, M6 Threaded
DOUBLE DENSITY 150 x 300 x 12.7 M6/26
AT205 Black Gaffa Foil Tape 50mm x 25m
0477-001 REV F Breadboard 200 mm x 200 mm x 12.7 mm
LIGHT DISPERSIVE SHIELD 24" x 12" (609.6 mm x 304.8 mm)
Sorbothane Feet, Ø45mm Female M6 Thread
750mm Side Shelf without Antistatic Protection
0691-001 REV F Breadboard 100 mm x 150 mm x 12.7 mm
Sorbathane Sheet, 12 x 12 x 1/4 Durometer 70
Monitor Mount with Articulating Arm
Aluminium Breadboard 450 x 150 x 12.7mm M6/25mm

Amb el suport de:

AT205 Black Gaffa Foil Tape 25mm x 25m
0737-001 REV D Breadboard 20cm x 25cm x 12.7mm
CURVED LIGHT DISPERSIVE SHIELD - 24x12
Ø1.5" x 750 mm Post for ScienceDesk Frames
Breadboard Lifting Handles (set of 2)
Light Dispersive Shield 24x6
Aluminium Breadboard 300 x 100 x 12.7mm M6/25mm
Breadboard 112.5mm x 112.5mm x 12.7mm
Sorbothane Feet, Ø38.1mm Female M6 Thread
Cable clamp
MINI FLEXI LIGHT
12" Beam Height Measurement Tool
6" Beam Height Measurement Tool
Sorbathane Sheet, 12 x12 x 1/8
12" x 12" Self Adhesive Sheet
3 Axis Controller and Knob Box for 1" Cerna Stages
Nikon CFI Fluor 10XW, 10X, NA 0.3, WD 3.5
Motorized Module with 1" Travel for Edge-Mounted Arms Cerna
200mm Large Insert Holder Rigid Stand
500mm Tall Cerna Functional Body
Kinematic Cage Cube, Right-Angle Mirror, Left-Hand, Metric
Kinematic Cage Cube, Right-Angle Mirror, Right-Hand, Metric
SM2 Threaded Fixed Arm for Cerna
SM1 Threaded Fixed Arm for Cerna
Leica Immersion Oil Very Low Auto Fluorescence, 10 ml
Single Objective Arm
GRIN Lens for 2P Imaging 1mm long
Cover Glass #1.5, 25mm Dia. 100 Pack
M32x0.75 External to M25x0.75 Internal
Fluorescent Slides, Set of 5
Fluorescent Calibration Microscope Slides, Green, Pack of 5
Ø2" Low GDD Mirror, 700 nm - 930 nm, 45° AOI
1" enhanced silver mirror, 750-1000nm, 45deg AOI
Replacement Fine Filter Set
Ultrafast 50/50 Beamsplitter 1 um - 2um
Torque Wrench, 5 lb-in
Coolflow DTX Coolant
Ø1" Spectral Responsivity Flattening Filter for FDS100
Ti:Sapphire Femtosecond laser

Amb el suport de: