



Ref.	Tipus	Cabell (l/s)	Dimensions (mm)	Diàmetre Connexió (mm)	Marca	Model
DC03	Difusor Circular amb plenum	50 – 180	356	249	TROX	ADLR/3
RI01	Reixa d'impulsió	111 – 417	825x125		TROX	AH–AG/825x125
RI02	Reixa d'impulsió	167 – 625	1025x165		TROX	AH–AG/1025x165
RR01	Reixa de Retorn	83 – 278	825x125		TROX	AH–AG/825x125
RR02	Reixa de Retorn	111 – 444	1225x125		TROX	AH–AG/1225x125
RR03	Reixa de Retorn	166 – 611	1225x165		TROX	AH–AG/1225x165
RE01	Reixa d'Extracció	0 – 277	225x75		TROX	AH–AG/225x75
RE02	Reixa d'Extracció	83 – 277	425x225		TROX	AH–AG/425x225
BE01	Boca d'Extracció	22 – 32	104	100	TROX	LVS/100/G1
CM01	Regulació manual aire primari	0 – 400	200	80	TROX	RN–80
CM02	Regulació manual aire primari	0 – 85	200	100	TROX	RN–100
	Comporta Tallafocs		(A+50)xB+50			
CC	Comporta Tallafocs en forja de sostre		(A+50)xB+50			
Ref Referència element l/s Cabell (l/s)						
Pref.	Material					
O	Conducte oval					
A	Xapa acer					
AA	Xapa acer allidada					
AH	Conducte estable a fums E600 120					
F	Fibra vidre					
HF	Conducte EI 120 (RF)					
P	Plàstic					

Legenda	SMBRILLO
	CIRCUIT IMPULSIO AIGUA FREDA
	CIRCUIT RETORN AIGUA FREDA
	CIRCUIT IMPULSIO AIGUA CALENTA
	CIRCUIT RETORN AIGUA CALENTA
	CIRCUIT IMPULSIO AIGUA CALENTA SANITARIA
	CIRCUIT RETORN AIGUA AIGUA CALENTA SANITARIA
	DELATADOR